

```
# www.phpmyfaq.de Apache configs, based on
# https://github.com/h5bp/server-configs-apache

# ######
# # CROSS-ORIGIN #
# ######

# -----
# / Cross-origin requests /
# -----


<IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
</IfModule>

# -----
# / Cross-origin images /
# -----


<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        <FilesMatch "\.(bmp|curl|gif|ico|jpe?|gl|png|svgz?|l|webp)$">
            SetEnvIf Origin ":" IS_CORS
            Header set Access-Control-Allow-Origin "*" env=IS_CORS
        </FilesMatch>
    </IfModule>
</IfModule>

# -----
# / Cross-origin web fonts /
# -----


<IfModule mod_headers.c>
    <FilesMatch "\.(eot|otf|tt[cf]|woff2?)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>

# ######
# # ERRORS #
# ######
```

```
# #####  
  
# -----  
# | Custom error messages/pages |  
# -----  
  
ErrorDocument 404 /errors/404.html  
  
# -----  
# | Error prevention |  
# -----  
  
Options -MultiViews  
  
# #####  
# # INTERNET EXPLORER #  
# #####  
  
# -----  
# | Document modes |  
# -----  
  
# Force Internet Explorer 8/9/10 to render pages in the highest mode  
# available in the various cases when it may not.  
#  
# https://hsivonen.fi/doctype/#ie8  
#  
# (!) Starting with Internet Explorer 11, document modes are deprecated.  
# If your business still relies on older web apps and services that were  
# designed for older versions of Internet Explorer, you might want to  
# consider enabling 'Enterprise Mode' throughout your company.  
#  
# http://msdn.microsoft.com/en-us/library/ie/bg182625.aspx#docmode  
# http://blogs.msdn.com/b/ie/archive/2014/04/02/stay-up-to-date-with-enterprise-mode-for-internet-explorer-11.aspx
```

```
<IfModule mod_headers.c>  
    Header set X-UA-Compatible "IE=edge"  
    <FilesMatch "\.  
(appcache|atom|bbaw|bmp|crxl|cssl|curl|eot|f4[abpv]|f1vl|geojson|gif|htc|icol|jpe?  
gl|jsl|json|ld)?
```

```

| m4|av|manifest|map|mp4|oex|og|agv|opus|otf|pdf|png|rdf|rss|safari|extz|svgz?
| swf|topojson|tt[cf]|txt|vcard|vcf|vtl|webappl|web[mp]|woff2?|x1|ocl|xml|xpi)">
    Header unset X-UA-Compatible
  </FilesMatch>
</IfModule>

# -----
# I Iframes cookies
# -----
# Allow cookies to be set from iframes in Internet Explorer.
#
# http://msdn.microsoft.com/en-us/library/ms537343.aspx
# http://www.w3.org/TR/2000/CR-P3P-20001215/

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVi TAIi PSA PSD
# IVai IVdi COHi HIS OUR IND CNT\""
# </IfModule>

# ######
# # MEDIA TYPES AND CHARACTERENCODINGS
# #
# #####
# -----
# I Media types
# -----
# Serve resources with the proper media types (f. k. a. MIME types).
#
# https://www.iana.org/assignments/media-types/media-types.xhtml
# https://httpd.apache.org/docs/current/mod/mod_mime.html#addtype

<IfModule mod_mime.c>

  # Data interchange

    AddType application/json json map topojson
    AddType application/ld+json jsonld
    AddType application/vnd.geo+json geojson
    AddType application/xml atom rdf rss xml

```

```
# JavaScript

# Normalize to standard type.
# https://tools.ietf.org/html/rfc4329#section-7.2

AddType application/javascript js

# Manifest files

# If you are providing a web application manifest file (see
# the specification: https://w3c.github.io/manifest/), it is
# recommended that you serve it with the `application/manifest+json`
# media type.
#
# Because the web application manifest file doesn't have its
# own unique file extension, you can set its media type either
# by matching:
#
# 1) the exact location of the file (this can be done using a
#    directive such as ``, but it will NOT work in
#    the `.htaccess` file, so you will have to do it in the main
#    server configuration file or inside of a ``
#    container)
#
#    e. g.:
#
#        <Location "/.well-known/manifest.json">
#            AddType application/manifest+json json
#        </Location>
#
# 2) the filename (this can be problematic as you will need to
#    ensure that you don't have any other file with the same name
#    as the one you gave to your web application manifest file)
#
#    e. g.:
#
#        <Files "manifest.json">
#            AddType application/manifest+json json
#        </Files>
```

```
AddType application/x-web-app-manifest+json      webapp
AddType text/cache-manifest                      appcache manifest
```

Media files

```
AddType audio/mp4                           f4a f4b m4a
AddType audio/ogg                           ogg ogg opus
AddType image/bmp                          bmp
AddType image/webp                         webp
AddType video/mp4                          f4v f4p m4v mp4
AddType video/ogg                          ogv
AddType video/webm                         webm
AddType video/x-flv                         f1v
AddType image/svg+xml                      svg svgz
```

```
# Serving '.ico' image files with a different media type
# prevents Internet Explorer from displaying them as images:
# https://github.com/h5bp/html5-
boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee
```

```
AddType image/x-icon                        cur ico
```

Web fonts

```
AddType application/font-woff                woff
AddType application/font-woff2                 woff2
AddType application/vnd.ms-fontobject        eot
```

```
# Browsers usually ignore the font media types and simply sniff
# the bytes to figure out the font type.
# https://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern
#
# However, Blink and WebKit based browsers will show a warning
# in the console if the following font types are served with any
# other media types.
```

```
AddType application/x-font-ttf               ttc ttf
AddType font/opentype                         otf
```

Other

```
AddType application/octet-stream safariextz
AddType application/x-bb-appworld bbaw
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpiinstall xpi
AddType text/vcard vcard vcf
AddType text/vnd.rim.location.xloc xloc
AddType text/vtt vtt
AddType text/x-component htc

</IfModule>

# -----
# / Character encodings
# -----
# -----



# Serve all resources labeled as `text/html` or `text/plain`
# with the media type `charset` parameter set to `UTF-8`.
#
# https://httpd.apache.org/docs/current/mod/core.html#adddefaultcharset

AddDefaultCharset utf-8

# -----
# Serve the following file types with the media type `charset`
# parameter set to `UTF-8`.
#
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addcharset

<IfModule mod_mime.c>
    AddCharset utf-8 .atom \
        .bbaw \
        .css \
        .geojson \
        .js \
        .json \
        .jsonld \
        .rdf \
        .rss \
        .topojson \

```

```
.vtt \
.webapp \
.xloc \
.xml

</IfModule>

# ######
# # REWRITES #
# #######

# -----
# I Rewrite engine /
# -----


<IfModule mod_rewrite.c>
    RewriteEngine On
    Options +FollowSymlinks
    RewriteBase /
</IfModule>

# -----
# I Forcing the `www.` at the beginning of URLs /
# -----


<IfModule mod_rewrite.c>
    RewriteCond %{HTTP_HOST} ^phpmyfaq.de$ 
    RewriteRule (.*) http://www.phpmyfaq.de/$1 [R=301,L]
</IfModule>

# ######
# # SECURITY #
# #######

# -----
# I Clickjacking /
# -----


<IfModule mod_headers.c>
    Header set X-Frame-Options "DENY"
    <FilesMatch "\.
(appcache\|atom\|bbaw\|bml\|crxl\|cssl\|curl\|eot\|f4[abpv]\|f1\|geo\|json\|gif\|htc\|ic\|jpe?

```

```
gl jsl json(1d)?  
| m4(av)| manifest mapl mp4l oexl og(av)| opusl ofl pdfl pngl rdfl rssl safariextzl svgz?  
| swfl topojsonl tt(cf)| txtl vcardl vcfl vttl webappl web(mp)| woff2?| x1ocl xml1 xpi)$">  
    Header unset X-Frame-Options  
  </FilesMatch>  
</IfModule>  
  
# ----- /  
# / File access  
# ----- /  
  
<IfModule mod_autoindex.c>  
    Options -Indexes  
</IfModule>  
  
<IfModule mod_rewrite.c>  
    RewriteEngine On  
    RewriteCond %{REQUEST_URI} "!(^/)\.well-known/([^.]+/.?)+$" [NC]  
    RewriteCond %{SCRIPT_FILENAME} -d [OR]  
    RewriteCond %{SCRIPT_FILENAME} -f  
    RewriteRule "(^/)\." - [F]  
</IfModule>  
  
<FilesMatch "(^#.*#\|.bak|conf|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|("$")$">  
  
    # Apache < 2.3  
    <IfModule !mod_authz_core.c>  
        Order allow,deny  
        Deny from all  
        Satisfy All  
    </IfModule>  
  
    # Apache ≥ 2.3  
    #<IfModule mod_authz_core.c>  
    #    Require all denied  
    #</IfModule>  
  
</FilesMatch>  
  
# ----- /  
# / Reducing MIME type security risks  
# ----- /
```

```
# -----  
  
<IfModule mod_headers.c>  
    Header set X-Content-Type-Options "nosniff"  
</IfModule>  
  
# #####  
# # WEB PERFORMANCE  
# #####  
  
# -----  
# / Compression  
# -----  
  
<IfModule mod_deflate.c>  
  
    <IfModule mod_setenvif.c>  
        <IfModule mod_headers.c>  
            SetEnvIfNoCase ^Accept-Encoding$ X-cept-Encoding $1 "(15)" -$(15)$  
            ^((gzip|deflate)\s*,\s*)+([X"-](4,13))$ HAVE_Accept-Encoding  
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding  
        </IfModule>  
    </IfModule>  
  
    <IfModule mod_filter.c>  
        AddOutputFilterByType DEFLATE "application/atom+xml" \  
            "application/javascript" \  
            "application/json" \  
            "application/ld+json" \  
            "application/manifest+json" \  
            "application/rdf+xml" \  
            "application/rss+xml" \  
            "application/schema+json" \  
            "application/vnd.geo+json" \  
            "application/vnd.ms-fontobject" \  
            "application/x-font-ttf" \  
            "application/x-javascript" \  
            "application/x-web-app-manifest+json" \  
            "application/xhtml+xml" \  
            "application/xml" \  
            "font/eot" \  
    </IfModule>
```

```
    "font/opentype" \
    "image/bmp" \
    "image/svg+xml" \
    "image/vnd.microsoft.icon" \
    "image/x-icon" \
    "text/cache-manifest" \
    "text/css" \
    "text/html" \
    "text/javascript" \
    "text/plain" \
    "text/vcard" \
    "text/vnd.rim.location.xloc" \
    "text/vtt" \
    "text/x-component" \
    "text/x-cross-domain-policy" \
    "text/xml"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
    AddEncoding gzip      svgz
</IfModule>
```

```
</IfModule>
```

```
# -----
# / ETags
# ----- /
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

```
FileETag None
```

```
# -----
# / Expires headers
# ----- /
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"

# CSS
ExpiresByType text/css "access plus 1 year"

# Data interchange
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rdf+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/schema+json "access plus 0 seconds"
ExpiresByType application/vnd.geo+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"

# Favicon (cannot be renamed!) and cursor images
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
ExpiresByType image/x-icon "access plus 1 week"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/manifest+json "access plus 1 year"

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media files
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/bmp "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web fonts

# Embedded OpenType (EOT)
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"

# OpenType
ExpiresByType font/opentype "access plus 1 month"

# TrueType
ExpiresByType application/x-font-ttf "access plus 1 month"

# Web Open Font Format (WOFF) 1.0
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"

# Web Open Font Format (WOFF) 2.0
ExpiresByType application/font-woff2 "access plus 1 month"

# Other
ExpiresByType text/x-cross-domain-policy "access plus 1 week"

</IfModule>

# -----
# Old www.phpmyfaq.de rewrites /
# -----

<IfModule mod_rewrite.c>

# API
RewriteRule json/version.php http://api.phpmyfaq.de/versions
[R=301,L]

```

```
RewriteRule api/version http://api.phpmyfaq.de/versions
[R=301,L]
RewriteRule api/verify/(.+)$ http://api.phpmyfaq.de/verify/$1
[L,QSA]

# Downloads
RewriteRule download/phpMyFAQ-latest.zip
http://download.phpmyfaq.de/phpMyFAQ-latest.zip [R=301,L]
RewriteRule download/phpMyFAQ-latest.tar.gz
http://download.phpmyfaq.de/phpMyFAQ-latest.tar.gz [R=301,L]
RewriteRule download/phpMyFAQ-development.zip
http://download.phpmyfaq.de/phpMyFAQ-development.zip [R=301,L]
RewriteRule download/phpMyFAQ-development.tar.gz
http://download.phpmyfaq.de/phpMyFAQ-development.tar.gz [R=301,L]
RewriteRule download/phpMyFAQ-(.+).zip$
http://download.phpmyfaq.de/phpMyFAQ-$1.zip [R=301,L]
RewriteRule download/phpMyFAQ-(.+).tar.gz$
http://download.phpmyfaq.de/phpMyFAQ-$1.tar.gz [R=301,L]
RewriteRule download/phpmyfaq-(.+).tar.gz.md5$
http://download.phpmyfaq.de/phpMyFAQ-$1.tar.gz.md5 [R=301,L]
RewriteRule download/phpmyfaq-(.+)&version=(.+)
http://download.phpmyfaq.de/phpmyfaq-$1&version=$2 [R=301,L]

# Documentation
RewriteRule documentation.([0-9]+).([0-9]+).en.php$ /docs/$1.$2 [R=301,L]

# News
RewriteRule news/([0-9]+).php$ /news/$1 [R=301,L]
RewriteRule ([0-9]+).php$ /news/$1 [R=301,L]

# Security Advisories
RewriteRule news/advisory_([0-9]+)-([0-9]+)-([0-9]+).php$ /security/advisory-$1-
$2-$3 [R=301,L]
RewriteRule security/advisory_([0-9]+)-([0-9]+)-([0-9]+).php$ /security/advisory-$1-
$2-$3 [R=301,L]
RewriteRule advisory_([0-9]+)-([0-9]+)-([0-9]+).php$ /security/advisory-$1-
$2-$3 [R=301,L]
RewriteRule advisoriesadvisory-([0-9]+)-([0-9]+)-([0-9]+) /security/advisory-$1-
$2-$3 [R=301,L]

</IfModule>
```

```
<IfModule mod_alias.c>
    # Permanent 301 redirects
    RedirectPermanent /10years.php /10years
    RedirectPermanent /bugtraq.php

https://github.com/thorsten/phpMyFAQ/issues
    RedirectPermanent /changelog.php /changelog
    RedirectPermanent /codenames.php /docs/codenames
    RedirectPermanent /docs/codenames.php /docs/codenames
    RedirectPermanent /codingguidelines.php /docs/standards
    RedirectPermanent /docs/standards.php /docs/standards
    RedirectPermanent /contributing.php /contribute
    RedirectPermanent /contribute.php /contribute
    RedirectPermanent /danke.php /thankyou
    RedirectPermanent /demo http://demo.phpmyfaq.de
    RedirectPermanent /download /download
    RedirectPermanent /development.php /development
    RedirectPermanent /dokumentation.php /documentation
    RedirectPermanent /documentation.php /documentation
    RedirectPermanent /dokumentation.1.0.de.php /docs
    RedirectPermanent /docs/dokumentation.1.0.de.php /docs
    RedirectPermanent /dokumentation.1.1.de.php /docs
    RedirectPermanent /docs/dokumentation.1.1.de.php /docs
    RedirectPermanent /dokumentation.1.2.php /docs
    RedirectPermanent /dokumentation.1.2.de.php /docs
    RedirectPermanent /docs/dokumentation.1.2.de.php /docs
    RedirectPermanent /dokumentation.1.3.cz.php /docs
    RedirectPermanent /dokumentation.1.3.de.php /docs
    RedirectPermanent /docs/dokumentation.1.3.cz.php /docs
    RedirectPermanent /docs/dokumentation.1.3.de.php /docs
    RedirectPermanent /dokumentation.1.3.en.php /docs
    RedirectPermanent /docs/dokumentation.1.3.en.php /docs
    RedirectPermanent /dokumentation.1.3.pl.php /docs
    RedirectPermanent /docs/dokumentation.1.3.pl.php /docs
    RedirectPermanent /dokumentation.1.4.en.php /docs
    RedirectPermanent /docs/dokumentation.1.4.en.php /docs
    RedirectPermanent /dokumentation.1.5.en.php /docs
    RedirectPermanent /docs/dokumentation.1.5.en.php /docs
    RedirectPermanent /dokumentation.1.6.en.php /docs
    RedirectPermanent /docs/dokumentation.1.6.en.php /docs
    RedirectPermanent /dokumentation.1.6.de.php /docs
```

```
RedirectPermanent /docs/dokumentation.1.6.de.php /docs
RedirectPermanent /dokumentation.2.0.en.php /docs/2.0
RedirectPermanent /docs/dokumentation.2.0.en.php /docs/2.0
RedirectPermanent /documentation.2.5.en.php /docs/2.5
RedirectPermanent /docs/documentation.2.5.en.php /docs/2.5
RedirectPermanent /documentation.2.6.en.php /docs/2.6
RedirectPermanent /docs/documentation.2.6.en.php /docs/2.6
RedirectPermanent /documentation.2.7.en.php /docs/2.7
RedirectPermanent /docs/documentation.2.7.en.php /docs/2.8
RedirectPermanent /docs/documentation.2.8.en.php /docs/2.8
RedirectPermanent /docs/documentation.de.html /documentation
RedirectPermanent /documentation.php /documentation
RedirectPermanent /docs/documentation.de.php /documentation
RedirectPermanent /docs/lizenz.html
```

<https://raw.github.com/thorsten/phpMyFAQ/master/LICENSE>

```
RedirectPermanent /docs/lizenz.php
https://raw.github.com/thorsten/phpMyFAQ/master/LICENSE
RedirectPermanent /docs/phpmyfaq.txt /docs
RedirectPermanent /donations.php /donations
RedirectPermanent /download.php /download
RedirectPermanent /download.PHP /download
RedirectPermanent /download_old.php /old-downloads
RedirectPermanent /faq http://faq.phpmyfaq.de
RedirectPermanent /features.php /features
RedirectPermanent /forum http://forum.phpmyfaq.de
RedirectPermanent /hosting.php /hosting
RedirectPermanent /impressum.php /imprint
RedirectPermanent /imprint.php /imprint
RedirectPermanent /index.php /
RedirectPermanent /lifecycle.php /
RedirectPermanent /license.php
```

<https://raw.github.com/thorsten/phpMyFAQ/master/LICENSE>

```
RedirectPermanent /lizenz.php
https://raw.github.com/thorsten/phpMyFAQ/master/LICENSE
RedirectPermanent /logo.php /
RedirectPermanent /mailingliste.php http://forum.phpmyfaq.de
RedirectPermanent /news/bugtraq.php
https://github.com/thorsten/phpMyFAQ/issues
```

```
RedirectPermanent /news/changelog.php /changelog
RedirectPermanent /news/documentation.php /documentation
RedirectPermanent /news/dokumentation.php /documentation
```

```
RedirectPermanent /news/documentation.1.3.php /documentation
RedirectPermanent /news/dokumentation.1.3.php /documentation
RedirectPermanent /news/dokumentation.1.3.pl.php /documentation
RedirectPermanent /documentation.php /documentation
RedirectPermanent /referenzen.php /references
RedirectPermanent /references.php /references
RedirectPermanent /requirements.php /requirements
RedirectPermanent /roadmap.php /
RedirectPermanent /security.php /advisories
RedirectPermanent /standards.php /docs/standards
RedirectPermanent /support.php /support
RedirectPermanent /team.php /imprint
RedirectPermanent /terms.php /terms
RedirectPermanent /themes.php /themes
RedirectPermanent /imprint.php /imprint
RedirectPermanent /translation.php /translations
RedirectPermanent /xml/faqschema.xsd /
RedirectPermanent /xml/version.php http://api.phpmyfaq.de/versions
```

```
</IfModule>
```

```
# -----
# I Redirects www.phpmyfaq.de/file.html to www.phpmyfaq.de/file
# -----
```

```
<IfModule mod_rewrite.c>
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_FILENAME}.html -f
    RewriteRule ^(.*)$ $1.html [L]
</IfModule>
```