

```
<FilesMatch "^(autohandler dhandler openss7-local-repol auth.pl)$">
    Order Deny,Allow
    Deny from all
</FilesMatch>
<FilesMatch "(\.lsm$|\.asc$|SUMSI KEY)">
    Order allow,deny
    Allow from all
    ForceType "text/plain"
</FilesMatch>
# All repo files are controlled by the autohandler
<IfModule mod_authn_dbm.c>
<FilesMatch
"^(OPENSS7credentials|credentials|openss7_repol|openss7_list|netrc|openss7|openss7_defs|openss7_mirrors)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "Client OpenSS7 Repository Access Credentials"
    AuthBasicProvider dbm
    AuthDBMType DB
    AuthDBMUUserFile /var/www/mason/repousers
    AuthDBMGroupFile /var/www/mason/repousers
    Require group owners subs guests hosts
    Satisfy all
    ForceType "text/plain"
    SetHandler perl-script
    PerlHandler HTML::Mason::ApacheHandler
</FilesMatch>
</IfModule>
<IfModule !mod_authn_dbm.c>
<FilesMatch
"^(OPENSS7credentials|credentials|openss7_repol|openss7_list|netrc|openss7|openss7_defs|openss7_mirrors)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "Client OpenSS7 Repository Access Credentials"
    AuthDBUUserFile /var/www/mason/repousers
    <!-- FOO -->
```

```
AuthnGroupType /var/www/mason/reposusers
Require group owners subs guests hosts
Satisfy all
ForceType "text/plain"
SetHandler perl-script
PerlHandler HTML::Mason::ApacheHandler
</FilesMatch>
</IfModule>
<IfModule mod_authn_dbm.c>
<FilesMatch "^(/OPENSSL/service|openssl|vendor|list|media|cfg|urpmi|cfg)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "Client OpenSS7 Repository Access Credentials"
    AuthBasicProvider dbm
    AuthDBMType DB
    AuthDBMUserFile /var/www/mason/reposusers
    AuthDBMGroupFile /var/www/mason/reposusers
    Require group hosts
    Satisfy all
    ForceType "text/plain"
    SetHandler perl-script
    PerlHandler HTML::Mason::ApacheHandler
</FilesMatch>
</IfModule>
<IfModule !mod_authn_dbm.c>
<FilesMatch "^(/OPENSSL/service|openssl|vendor|list|media|cfg|urpmi|cfg)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "Client OpenSS7 Repository Access Credentials"
    AuthDBUserFile /var/www/mason/reposusers
    AuthDBGroupFile /var/www/mason/reposusers
    Require group hosts
    Satisfy all
    ForceType "text/plain"
    SetHandler perl-script
    PerlHandler HTML::Mason::ApacheHandler
</FilesMatch>
</IfModule>
```

```
</IfModule>
<Files "mirrorlist">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    ForceType "text/plain"
    SetHandler perl-script
    PerlHandler HTML::Mason::ApacheHandler
</Files>
# xml files must only be downloaded by machines (but any machine)
<IfModule mod_authn_dbm.c>
<FilesMatch "\.xml(\.gz)?$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthBasicProvider dbm
    AuthDBMType DB
    AuthDBMUserFile /var/www/mason/reposusers
    AuthDBMGroupFile /var/www/mason/reposusers
    PerlRequire /var/www/mason/perl/auth.pl
    PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
    Require group hosts
</FilesMatch>
</IfModule>
<IfModule !mod_authn_dbm.c>
<FilesMatch "\.xml(\.gz)?$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthDBUserFile /var/www/mason/reposusers
    AuthDBGroupFile /var/www/mason/reposusers
    PerlRequire /var/www/mason/perl/auth.pl
    PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
    Require group hosts
</FilesMatch>
</IfModule>
# apt meta files must only be downloaded by machines (but any machine)
```

```
<IfModule mod_authn_dbm.c>
<FilesMatch "^((Packages|Sources|Contents|Release)\.gz|\.bz2|\.gpg|\.key)?( md5sum\.txt)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthBasicProvider dbm
    AuthDBMType DB
    AuthDBMUserFile /var/www/mason/reposusers
    AuthDBMGroupFile /var/www/mason/reposusers
    PerlRequire /var/www/mason/perl/auth.pl
    PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
    Require group hosts
</FilesMatch>
</IfModule>
<IfModule !mod_authn_dbm.c>
<FilesMatch "^((Packages|Sources|Contents|Release)\.gz|\.bz2|\.gpg|\.key)?( md5sum\.txt)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthDBUserFile /var/www/mason/reposusers
    AuthDBGroupFile /var/www/mason/reposusers
    PerlRequire /var/www/mason/perl/auth.pl
    PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
    Require group hosts
</FilesMatch>
</IfModule>
# repoindex.xml only downloaded by machines with correct credentials
<IfModule mod_authn_dbm.c>
<Files "repoindex.xml">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthBasicProvider dbm
    AuthDBMType DB
    AuthDBMUserFile /var/www/mason/reposusers
```

```
AuthDBMGroupFile /var/www/mason/repousers
Require group zypp-hosts
Satisfy all
ForceType "text/plain"
SetHandler perl-script
PerlHandler HTML::Mason::ApacheHandler
</Files>
</IfModule>
<IfModule ! mod_authn_dbm.c>
<Files "repoindex.xml">
Order allow,deny
Allow from all
SSLRequireSSL
AuthType Basic
AuthName "OpenSS7 Repository Host Access Credentials"
AuthDBUserFile /var/www/mason/repousers
AuthDBGroupFile /var/www/mason/repousers
Require group zypp-hosts
Satisfy all
ForceType "text/plain"
SetHandler perl-script
PerlHandler HTML::Mason::ApacheHandler
</Files>
</IfModule>
# RPMs or DEBs (other than openss7-repo) must only be downloaded by machines
# RPMs or DEBs must be overridden to allow guests-hosts in individual subdirectories
<IfModule mod_authn_dbm.c>
<FilesMatch "^openss7-[^r].*\.(rpm|u?d?deb|pkg|tar|xz(\.sig)?)$">
Order allow,deny
Allow from all
SSLRequireSSL
AuthType Basic
AuthName "OpenSS7 Repository Host Access Credentials"
AuthBasicProvider dbm
AuthDBMType DB
AuthDBMUserFile /var/www/mason/repousers
AuthDBMGroupFile /var/www/mason/repousers
PerlRequire /var/www/mason/perl/auth.pl
PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
Require group hosts
</FilesMatch>
```

```
</IfModule>
<IfModule ! mod_authn_dbm.c>
<FilesMatch "^openss7-[^r].*\.(rpm|u?d?deb|pkg|tar|xz(\.sig)?)$">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Host Access Credentials"
    AuthDBUserFile /var/www/mason/reposusers
    AuthDBGroupFile /var/www/mason/reposusers
    PerlRequire /var/www/mason/perl/auth.pl
    PerlAuthenHandler OpenSS7::Auth::rpmauthenhandler
    Require group hosts
</FilesMatch>
</IfModule>
# Anybody can download the repository RPMs or DEBs
<FilesMatch "^openss7-repo.*\.(rpm|u?d?deb|pkg|tar|xz(\.sig)?)$">
    Order allow,deny
    Allow from all
</FilesMatch>
# tarballs and spec files must only be downloaded by subscribers
# must be overridden to allow guests
<IfModule mod_authn_dbm.c>
<FilesMatch "^openss7-1\..*[0-9]\.(tar|gz|bz2|xz|lzma)|spec|src|rpml|dsc(\.asc)?|\.\.src|tar|xz(\.sig)?">
    Order allow,deny
    Allow from all
    SSLRequireSSL
    AuthType Basic
    AuthName "OpenSS7 Repository Subscriber Access Credentials"
    AuthBasicProvider file
    AuthUserFile /etc/httpd/passwd
    AuthGroupFile /etc/httpd/group
    Require group owners subs
</FilesMatch>
</IfModule>
<IfModule ! mod_authn_dbm.c>
<FilesMatch "^openss7-1\..*[0-9]\.(tar|gz|bz2|xz|lzma)|spec|src|rpml|dsc(\.asc)?|\.\.src|tar|xz(\.sig)?">
    Order allow,deny
    Allow from all
```

```
SSLRequireSSL
AuthType Basic
AuthName "OpenSS7 Repository Subscriber Access Credentials"
AuthUserFile /etc/httpd/passwd
AuthGroupFile /etc/httpd/group
Require group owners subs
</FilesMatch>
</IfModule>
```