

```
#
# Apache/PHP/Drupal settings:
#
# Protect files and directories from prying eyes.
<FilesMatch "\.(engine|incl|info|install|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?
|xtmpl|svn-base)|\.(code-style|.pl|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0
    php_value session.auto_start 0
    php_value mbstring.http_input pass
    php_value mbstring.http_output pass
    php_value mbstring.encoding_translation 0
</IfModule>
```

PHP 4, Apache 2.

```
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc                0
    php_value register_globals                0
    php_value session.auto_start             0
    php_value mbstring.http_input            pass
    php_value mbstring.http_output           pass
    php_value mbstring.encoding_translation  0
</IfModule>
```

PHP 5, Apache 1 and 2.

```
<IfModule mod_php5.c>
    php_value magic_quotes_gpc                0
    php_value register_globals                0
    php_value session.auto_start             0
    php_value mbstring.http_input            pass
    php_value mbstring.http_output           pass
    php_value mbstring.encoding_translation  0
</IfModule>
```

Requires mod_expires to be enabled.

```
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

    # Do not cache dynamically generated pages.
    ExpiresByType text/html A1
</IfModule>
```

Various rewrite rules.

```
<IfModule mod_rewrite.c>
    RewriteEngine on

    # If your site can be accessed both with and without the 'www.' prefix, you
    # can use one of the following settings to redirect users to your preferred
    # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
    #
    # - Redirect to the 'www.' prefix:
    # RewriteRule ^(.*)$ http://www/$1 [R=301,L]
```

```
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# adapt and uncomment the following:
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment and adapt the following:
RewriteCond %{HTTP_HOST} ^www\.(2u4u)\.com.cn$ [NC]
RewriteRule ^(.*)$ http://2u4u.com.cn/$1 [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.90.2.3 2008/12/10 20:04:08 goba Exp $
```