

```
#####
# Encoding UTF-8 para todo

AddDefaultCharset utf-8
AddCharset utf-8 .htm .html .css .js .xml .json .rss .txt

# Quita Directory Browsing
Options -Indexes

#####
# Caché General de Estáticos (Cache-Control)
<IfModule mod_headers.c>

    FileETag MTime Size

    <FilesMatch "^.*\.(ico|pdf|flv|jpg|jpeg|png|gif|bmp|swf|mp3|mp4|ttf|woff|svg|eot)$">
        Header set Cache-Control "public, no-transform"
        #Header unset Last-Modified
        FileETag MTime Size
    </FilesMatch>

</IfModule>

#####
# Expires Específicos
<IfModule mod_expires.c>

    ExpiresActive on

    # Las imágenes se pueden cachear agresivamente
    ExpiresByType image/bmp      "access plus 1 year"
    ExpiresByType image/png      "access plus 1 year"
    ExpiresByType image/gif      "access plus 1 year"
    ExpiresByType image/jpg      "access plus 1 year"
    ExpiresByType image/jpeg     "access plus 1 year"

    # Setea los tipos de fonts en Apache
    AddType application/vnd.ms-fontobject eot
    AddType font/truetype         ttf
    AddType font/opentype         otf
    AddType font/woff             woff
```

```
HeaderType font/woff
```

```
woff
```

```
# Las fonts también se cachean agresivamente
```

```
ExpiresByType application/octet-stream "access plus 1 year"  
ExpiresByType application/vnd.ms-fontobject "access plus 1 year"  
ExpiresByType font/truetype "access plus 1 year"  
ExpiresByType font/opentype "access plus 1 year"  
ExpiresByType font/woff "access plus 1 year"
```

```
# El CSS y JS puede que cambie, así que se pone una vez a la semana.
```

```
ExpiresByType text/css "access plus 1 week"  
ExpiresByType text/javascript "access plus 1 week"  
ExpiresByType application/javascript "access plus 1 week"  
ExpiresByType text/plain "access plus 1 week"
```

```
# MIME type especial para favicons - see http://www.iana.org/assignments/media-types/image/vnd.microsoft.icon
```

```
AddType image/vnd.microsoft.icon ico
```

```
# Los favicons se cachean medianamente
```

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 month"
```

```
</IfModule>
```

```
#####
```

```
# Compresión de CSS y JS
```

```
<IfModule mod_deflate.c>
```

```
AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
```

```
AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-  
javascript
```

```
AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
SetOutputFilter DEFLATE
```

```
# Don't compress
```

```
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip dont-vary
```

```
SetEnvIfNoCase Request_URI \.(?:exe|t?gz|zip|bz2|sit|rar)$ no-gzip dont-vary
```

```
#Dealing with proxy servers
```

```
<IfModule mod_headers.c>
```

```
Header always set Cache-Control "max-age=3600, private, no-store, no-cache, must-revalidate, proxy-rewrite"
```

```
Header append Vary User-Agent
</IfModule>
</IfModule>
```

```
ServerSignature Off
```