

```
Options +FollowSymlinks -Indexes
```

```
AddDefaultCharset off
```

```
AddType application/x-httpd-php .apache
```

```
<IfModule mod_php5.c>
```

```
    php_value short_open_tag 1
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine on
```

```
    # You may need RewriteBase on some servers (debian). NOTE: / is document root.  
    #RewriteBase /
```

```
    # Rewrite resource URIs to minify
```

```
    RewriteRule ^js/(.*\.js)$ min/?g=$1 [NE]
```

```
    RewriteRule ^css/(.*\.css)$ min/?g=$1 [NE]
```

```
    RewriteRule ^css/(.*\.less)$ min/?g=$1 [L,NE]
```

```
    # Rewrite help URIs to minify
```

```
    #RewriteRule ^help(/)?$ help [L,NE]
```

```
    # Rewrite sms callbacks
```

```
    RewriteRule ^sms/callback/([0-9]+)(.*)$ sms/handle.php?request=callback&user=$1&$2
```

```
[QSA, L]
```

```
    # Location request - images
```

```
    RewriteCond %{SCRIPT_FILENAME} !-d
```

```
    RewriteCond %{SCRIPT_FILENAME} !-f
```

```
    RewriteRule ^1/.*img/(.*)$ img/$1 [L]
```

```
    # Location request
```

```
    RewriteCond %{SCRIPT_FILENAME} !-d
```

```
    RewriteCond %{SCRIPT_FILENAME} !-f
```

```
    RewriteRule ^1/(.*)$ trace/locate.php?id=$1 [L]
```

Location request - appcache

RewriteCond %{SCRIPT_FILENAME} !-d

RewriteCond %{SCRIPT_FILENAME} !-f

RewriteRule ^1/(.*)/. *appcache\$ trace/locate_appcache.php?id=\$1 [L]

Location request - abort

RewriteCond %{SCRIPT_FILENAME} !-d

RewriteCond %{SCRIPT_FILENAME} !-f

RewriteRule ^a/(.*)\$ trace/abort.php?id=\$1 [L]

Location report

RewriteCond %{SCRIPT_FILENAME} !-d

RewriteCond %{SCRIPT_FILENAME} !-f

RewriteRule ^r/(.*)/(.*)/(.*)/(.*)/(.*)/(.*)\$ trace/report.php?id=\$1&lat=\$2&lon=\$3&acc=\$4&alt=\$5×tamp=\$6 [L]

</IfModule>