

```
#  
# Apache/PHP/Drupal settings:  
#  
  
# Protect files and directories from prying eyes.  
<FilesMatch "\.\.(engine|include|install|make|module|profile|test|sql|theme|tpl(\.|php)|xtmpl|svn-base)$|^(code-style|Entries|Repository|Root|Tag|Template|all-wcprops|entries|format)$">  
    Order allow,deny  
</FilesMatch>  
  
# Don't show directory listings for URLs which map to a directory.  
Options -Indexes  
  
# Follow symbolic links in this directory.  
Options +FollowSymLinks  
  
# Make Drupal handle any 404 errors.  
ErrorDocument 404 /index.php  
  
# Force simple error message for requests for non-existent favicon.ico.  
<Files favicon.ico>  
    # There is no end quote below, for compatibility with Apache 1.3.  
    ErrorDocument 404 "The requested file favicon.ico was not found."  
</Files>  
  
# Set the default handler.  
DirectoryIndex index.php  
  
# Override PHP settings. More in sites/default/settings.php  
# but the following cannot be changed at runtime.  
  
# PHP 4, Apache 1.  
<IfModule mod_php4.c>  
    php_value magic_quotes_gpc          0  
    php_value register_globals         0  
    php_value session.auto_start      0  
    php_value mbstring.http_input     pass  
    php_value mbstring.http_output    pass  
    php_value mbstring.encoding_error 0
```

```
php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    php_value mbstring.http_output     pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    php_value mbstring.http_output     pass
    php_value mbstring.encoding_translation 0
</IfModule>

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

    <FilesMatch \.php$>
        # Do not allow PHP scripts to be cached unless they explicitly send cache
        # headers themselves. Otherwise all scripts would have to overwrite the
        # headers set by mod_expires if they want another caching behavior. This may
        # fail if an error occurs early in the bootstrap process, and it may cause
        # problems if a non-Drupal PHP file is installed in a subdirectory.
        ExpiresActive Off
    </FilesMatch>
</IfModule>
```

```
# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine on

    # If your site can be accessed both with and without the 'www.' prefix, you
    # can use one of the following settings to redirect users to your preferred
    # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
    #

    # To redirect all users to access the site WITH the 'www.' prefix,
    # (http://example.com/...) will be redirected to http://www.example.com/...)
    # adapt and uncomment the following:
    # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
    # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
    #

    RewriteCond %{HTTP_HOST} ^finisteretourisme\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/$1 [L,R=301]

    RewriteCond %{HTTP_HOST} ^finistere-tourisme\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/$1 [L,R=301]

    RewriteCond %{HTTP_HOST} ^www\.finistere-tourisme\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/$1 [L,R=301]

    RewriteCond %{HTTP_HOST} ^finistere-nautisme\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/decouvrez/activites-nautiques
[L,R=301]

    RewriteCond %{HTTP_HOST} ^finistere-randonnees\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/decouvrez/randonnees-pour-tous/
[L,R=301]

    RewriteCond %{HTTP_HOST} ^finistere-enfamille\.com$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/$1 [L,R=301]

    RewriteCond %{HTTP_HOST} ^cdt-finistere\.fr$ [NC]
    RewriteRule ^(.*) http://www.finisteretourisme.com/$1 [L,R=301]

    RewriteCond %{HTTP_HOST} ^en\.finisteretourisme\.com$ [NC]
    RewriteRule ^(.*) http://www.finisterebrittany.com/$1 [L,R=301]
```

```
RewriteCond %{HTTP_HOST} ^finistere-booking\.com$ [NC]
RewriteRule ^(.*.) http://www.finisterebrittany.com/book-your-stay-brittany [L,R=301]

RewriteCond %{HTTP_HOST} ^tourism-brittany\.com$ [NC]
RewriteRule ^(.*.) http://www.finisterebrittany.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^www\.tourism-brittany\.com$ [NC]
RewriteRule ^(.*.) http://www.finisterebrittany.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^www\.finistere-booking\.com$ [NC]
RewriteRule ^(.*.) http://www.finisterebrittany.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^tourism-brittany\.com$ [NC]
RewriteRule ^(.*.) http://www.tourism-brittany.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^finistere-booking\.com$ [NC]
RewriteRule ^(.*.) http://www.finistere-booking.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^finistere-dispo\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/reservez-et-organisez-votre-sejour-en-finistere [L,R=301]

RewriteCond %{HTTP_HOST} ^www\.finistere-dispo\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/reservez-et-organisez-votre-sejour-en-finistere [L,R=301]

RewriteCond %{HTTP_HOST} ^finistere-dispo\.com$ [NC]
RewriteRule ^(.*.) http://www.finistere-dispo.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^finistere-resa\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/reservez-et-organisez-votre-sejour-en-finistere [L,R=301]

RewriteCond %{HTTP_HOST} ^www\.finistere-resa\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/reservez-et-organisez-votre-sejour-en-finistere [L,R=301]

RewriteCond %{HTTP_HOST} ^www\.reservation-finistere\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/reservez-et-organisez-votre-sejour-en-finistere [L,R=301]
```

```
RewriteCond %{HTTP_HOST} ^newweb.finisteretourisme\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^en.newweb.finisteretourisme\.com$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/$1 [L,R=301]

RewriteCond %{HTTP_HOST} ^monfinistere\.fr$ [NC]
RewriteRule ^(.*.) http://www.finisteretourisme.com/concours-photos-mon-finistere
[L,R=301]

# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment and adapt the following:
# RewriteCond %{HTTP_HOST} ^www\.\example\.com$ [NC]
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L, QSA]
</IfModule>

# $Id$
```