

```
# handle any 404 errors,
ErrorDocument 404 /index.php

# apache
<IfModule mod_rewrite.c>
    RewriteEngine on
    # in this case, our app bootstrap file is index.php
    RewriteRule !\.(js|html|ico|gif|jpg|jpeg|png|css|less|pdf|xml)$ index.php
</IfModule>

AddDefaultCharset utf-8

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>

    # to activate mode_expires
    ExpiresActive on

    ExpiresDefault "access plus 1 month"

    # For CSS
    ExpiresByType text/css "access plus 1 month"

    # For Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

    # For Favicon
    ExpiresByType image/x-icon "access plus 1 year"

    # For HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"

    # For HTML
    ExpiresByType text/html "access plus 1 month"

    # For JavaScript
    ExpiresByType application/javascript "access plus 1 month"

    # For Manifest files
```

```

# For Manifest Files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# For Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# For Web feeds
ExpiresByType application/atom+xml "access plus 1 day"
ExpiresByType application/rss+xml "access plus 1 day"

# For Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
</IfModule>

# Enable Gzip compression.
<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# http://httpd.apache.org/docs/2.3/mod/mod_deflate.html)

```

*# as AddOutputFilterByType is still in the core directives).*

```
AddOutputFilterByType DEFLATE application/atom+xml \  
    application/javascript \  
    application/json \  
    application/rss+xml \  
    application/vnd.ms-fontobject \  
    application/x-font-ttf \  
    application/x-web-app-manifest+json \  
    application/xhtml+xml \  
    application/xml \  
    font/opentype \  
    image/svg+xml \  
    image/x-icon \  
    text/css \  
    text/html \  
    text/plain \  
    text/x-component \  
    text/xml
```

</IfModule>