

```
Options -MultiViews
```

```
AddHandler x-mapp-php6 .php
```

```
#  
# Dream Forgery Settings;  
#  
  
# Set some options.  
Options -Indexes  
Options +FollowSymLinks  
  
# Customized error messages.  
ErrorDocument 404 /404-error  
  
# Set the default handler.  
DirectoryIndex index.php  
  
#  
#ExpiresActive On  
#ExpiresByType image/jpg "access plus 1 hour"  
#ExpiresByType image/jpeg "access plus 1 hour"  
#ExpiresByType image/gif "access plus 1 hour"  
#ExpiresByType image/png "access plus 1 hour"  
#ExpiresDefault "access plus 1 hour"  
  
# Override PHP settings. More exist in sites/default/settings.php, but  
# the following cannot be changed at runtime. The first IfModule is  
# for Apache 1.3, the second for Apache 2.  
<IfModule mod_php4.c>  
    php_value magic_quotes_gpc          0  
    php_value register_globals          0  
    php_value session.auto_start        0  
</IfModule>  
  
<IfModule sapi_apache2.c>  
    php_value magic_quotes_gpc          0  
    php_value register_globals          0  
    php_value session.auto_start        0  
</IfModule>
```

```
# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on
  RewriteBase /

  # Rewrite current-style URLs of the form 'index.php?q=x'.
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^files/(.*)$ /webapp/files/$1 [L,QSA]

  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^(.*)$ /index.php?q=$1 [L,QSA]

  RewriteCond %{SERVER_PORT} ^80$
  RewriteRule .* https://%{SERVER_NAME}%{REQUEST_URI} [R,L]
</IfModule>
```