

```

<IfModule mod_rewrite.c>
  # Allow from all
  # Options All
  # AllowOverride All
  # RewriteCond %{SERVER_PORT}s ^(443(s)|[0-9]+s)$
  # RewriteRule ^(.*)$ - [env=askapache:%2]

  # # HTTPS -----
  # RewriteEngine On
  # RewriteCond %{HTTPS} !=on
  # RewriteRule ^ https://%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
  # # END HTTPS -----

  # Adaptive-Images -----

  Options +FollowSymlinks

  # Add any directories you wish to omit from the Adaptive-Images process on a new line, as
  # RewriteCond %{REQUEST_URI} !ignore-this-directory
  # RewriteCond %{REQUEST_URI} !and-ignore-this-directory-too

  RewriteCond %{REQUEST_URI} !assets
  # don't apply the AI behaviour to images inside AI's cache folder:
  RewriteCond %{REQUEST_URI} !ai-cache
  # Send any GIF, JPG, or PNG request that IS NOT stored inside one of the above directorie:
  # to adaptive-images.php so we can select appropriately sized versions
  RewriteRule \.(?:jpe?gl gifl png)$ adaptive-images.php
  # RewriteRule .(?:jpe?gl gifl png)$ test.jpg

  # END Adaptive-Images -----

  # Options +FollowSymlinks

  # # Start the rewrite engine
  # RewriteEngine On
  # RewriteBase /

  #
#####
  # # REDIRECT ANY DIRECT IMAGE REQUEST TO A CACHED VERSION
  " "

```

```

# #
# # You may add files or directories that shouldn't be touched by squeezeR like this:
# #
# # RewriteCond %{REQUEST_URI} !path/to/some/file-or-directory
# #
# # Please refer to the mod_rewrite documentation at http://httpd.apache.org/docs/2.2/mod\_
for
# # further possibilities and instructions.
# #
#####

# RewriteCond %{REQUEST\_FILENAME} -f
# RewriteCond %{ENV:REDIRECT\_BREAKPOINT} !\d+px
# RewriteCond %{QUERY\_STRING} !^\(\[\^&\]\*&\)\*squeezeR=\(0|false|no\)
# RewriteCond %{HTTP\_COOKIE} squeezeR.images=\(\d+px\) \[NC\]
# RewriteRule ^\(.+\)\(\.\(?:jpe?g|gif|png\)\)\$ squeezeR/cache/\$1-%1\$2 \[NC,E=BREAKPOINT:%1,L\]
# RewriteRule .\(\.\(?:jpe?g|gif|png\)\)\$ test.jpg
# # #####
#####

# # Please make sure that you set this path ^ to the squeezeR root directory that
specified
# # for the SQUEEZR\_ROOT constant in the common engine configuration \(SQUEEZR\_ROOT/conf/cu
# # apply the default setup for squeezeR \(i.e. put everything into a directory named "sque
# # website's document root\), then you shouldn't have to change anything.
#
#####

#
#####

# # REDIRECT ANY DIRECT CSS REQUEST TO A CACHED VERSION
# #
# # See above for some hints about excluding files or directories from the squeezeR proces
# #
#####

# RewriteCond %{REQUEST\_FILENAME} -f
# RewriteCond %{ENV:REDIRECT\_BREAKPOINT} !\d+px
# RewriteCond %{QUERY\_STRING} !^\(\[\^&\]\*&\)\*squeezeR=\(0|false|no\)
# RewriteCond %{HTTP\_COOKIE} squeezeR.css=\(\d+x\d+@\d+\(?:\.\d+\)?\) \[NC\]
# RewriteRule ^\(.+\)\.css\$ squeezeR/cache/\$1-%1.css \[NC,E=BREAKPOINT:%1,L\]
# RewriteRule ^\(.+\)\.css\$ squeezeR/cache/\$1-%1.css \[NC,E=BREAKPOINT:%1,L\]
# # #####
#####

```

```
.....

# # See above for hints on this path.
#
#####

RewriteRule ^index\.php$ - [L]
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(REQUEST_FILENAME) !-f
RewriteRule (.*) index.php/$1 [L]

</IfModule>

#
#####
# # Additional stuff for improving your website's delivery performance
#
#####

# # Deflating for text files (not required for squeezer, but recommended anyway)
# <IfModule mod_deflate.c>
#     AddOutputFilterByType DEFLATE text/plain text/html text/xml text/css text/javascript
#     json text/x-json-stream application/x-javascript application/json application/x-json
#     application/stream application/*.*xml.* multipart/x-json-stream multipart/x-mixed-replace image/svg+xml
# </IfModule>

# # Various expiration headers for proper file caching (not required for squeezer, but recommended)
# <IfModule mod_expires.c>

#     ExpiresActive on

#     # Images
#     ExpiresByType image/gif "access plus 35 days"
#     ExpiresByType image/png "access plus 35 days"
#     ExpiresByType image/jpg "access plus 35 days"
#     ExpiresByType image/jpeg "access plus 35 days"

#     # Text based files
#     ExpiresByType text/css "access plus 35 days"
#     ExpiresByType text/xml "access plus 35 days"
```

```
# ExpiresByType text/javascript "access plus 35 days"
# ExpiresByType application/x-shockwave-flash "access plus 35 days"

# # Default expiration
# ExpiresDefault "access plus 1 days"

# </IfModule>
```