

*# Ponemos el entorno en modo depuracion. Para ponerlo en produccion cambiar a 0.*

```
SetEnv MARIFA_DEBUG 0
```

*# Directivas de seguridad.*

```
<IfModule mod_access.c>
```

```
    # Bloqueo acceso al htaccess
```

```
    <Files .htaccess>
```

```
        Order allow,deny
```

```
        Deny from all
```

```
    </Files>
```

```
</IfModule>
```

*# Desactivo el listado de directorios.*

```
Options -Indexes
```

*# Eliminamos ETags.*

```
FileETag none
```

*# Agregamos mimes para deflate.*

```
<IfModule mod_mime.c>
```

```
    # JavaScript
```

```
    # Normalize to standard type (it's sniffed in IE anyways)
```

```
    # tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript js jsonp
```

```
AddType application/json json
```

```
    # Audio
```

```
AddType audio/ogg oga ogg
```

```
AddType audio/mp4 m4a f4a f4b
```

```
    # Video
```

```
AddType video/ogg ogv
```

```
AddType video/mp4 mp4 m4v f4v f4p
```

```
AddType video/webm webm
```

```
AddType video/x-flv flv
```

```
    # SVG
```

```
    # Required for svg webfonts on iPad
```

```
    # twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz
```

```
    # Add support for the new
```

```
HeaderEncoding gzip svgz
```

```
# Webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-font-ttf ttf ttc
```

```
AddType font/opentype otf
```

```
AddType application/x-font-woff woff
```

```
# Assorted types
```

```
AddType image/x-icon ico
```

```
AddType image/webp webp
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/x-component htc
```

```
AddType application/xml rss atom xml rdf
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/octet-stream safariextz
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType text/x-vcard vcf
```

```
AddType application/x-shockwave-flash swf
```

```
AddType text/vtt vtt
```

```
</IfModule>
```

```
# Activamos optimizaciones de cache.
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive On
```

```
ExpiresByType application/json "access plus 1 year"
```

```
ExpiresByType application/pdf "access plus 1 year"
```

```
ExpiresByType application/x-shockwave-flash "access plus 1 year"
```

```
ExpiresByType image/bmp "access plus 1 year"
```

```
ExpiresByType image/gif "access plus 1 year"
```

```
ExpiresByType image/jpeg "access plus 1 year"
```

```
ExpiresByType image/png "access plus 1 year"
```

```
ExpiresByType image/svg+xml "access plus 1 year"
```

```
ExpiresByType image/tiff "access plus 1 year"
```

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 year"
```

```
ExpiresByType image/x-icon "access plus 1 year"
```

```
ExpiresByType text/css "access plus 1 year"
```

```
ExpiresByType video/x-flv "access plus 1 year"
```

```
ExpiresByType video/x-m4v "access plus 1 year"
```

```
ExpiresByType application/vnd.bw-fontobject "access plus 1 year"
ExpiresByType application/x-font-ttf "access plus 1 year"
ExpiresByType application/font-woff "access plus 1 year"
ExpiresByType font/opentype "access plus 1 year"
ExpiresByType image/webp "access plus 1 year"
```

```
# The following MIME types are in the process of registration
```

```
ExpiresByType application/xslt+xml "access plus 1 year"
ExpiresByType image/svg+xml "access plus 1 year"
```

```
# The following MIME types are NOT registered
```

```
ExpiresByType application/mathml+xml "access plus 1 year"
ExpiresByType application/rss+xml "access plus 1 year"
```

```
# JavaScript has various MIME types
```

```
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType text/ecmascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"
```

```
</IfModule>
```

```
# Borraremos cabeceras si procedemos de un proxy.
```

```
<IfModule mod_headers.c>
```

```
# Try removing etag headers (if it's coming from proxy for example)
```

```
Header unset ETag
```

```
</IfModule>
```

```
# Configuraciones de la reescritura.
```

```
<IfModule mod_rewrite.c>
```

```
# Habilitamos la reescritura.
```

```
RewriteEngine On
```

```
# Directorio de la instalacion.
```

```
RewriteBase /
```

```
# Instalador.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteRule ^installer/. * installer.php/$0 [L]
```

```
# Permitimos archivos y directorios mostrarse directamente.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d  
  
# Enviamos el resto a index.php/URL  
RewriteRule .* index.php/$0 [PT]  
</IfModule>
```