

```
##  
#RewriteEngine On  
## The following rule tells Apache that if the requested filename  
## exists, simply serve it.  
#RewriteCond %{REQUEST_FILENAME} -s [OR]  
#RewriteCond %{REQUEST_FILENAME} -l [OR]  
#RewriteCond %{REQUEST_FILENAME} -d  
#RewriteRule ^.*$ - [NC,L]  
## The following rewrites all other queries to index.php. The  
## condition ensures that if you are using Apache aliases to do  
## mass virtual hosting, the base path will be prepended to  
## allow proper resolution of the index.php file; it will work  
## in non-aliased environments as well, providing a safe, one-size  
## fits all solution.  
#RewriteCond %{REQUEST_URI} ::$1 ~^(/.+)(.+)::$  
#RewriteRule ^(.*)$ - [E=BASE: %1]  
#RewriteRule ^(.*)$ %{ENV: BASE}index.php [NC,L]  
#  
AddDefaultCharset UTF-8  
<IfModule mod_rewrite.c>  
    RewriteEngine On  
    RewriteCond %{REQUEST_FILENAME} -s [OR]  
    RewriteCond %{REQUEST_FILENAME} -l [OR]  
    RewriteCond %{REQUEST_FILENAME} -d  
    RewriteRule ^.*$ - [NC,L]  
    RewriteRule ^.*$ index.php [NC,L]  
    RewriteRule ^index.php/\d+-(.+)$ $1 [R,L]  
</IfModule>
```