

```
SetEnv APPLICATION_ENV production
```

```
RewriteEngine On
```

```
RewriteCond %{HTTP_USER_AGENT} libwww-perl.*
```

```
RewriteRule .* - [F,L]
```

```
# The following rule tells Apache that if the requested filename  
# exists, simply serve it.
```

```
RewriteRule \.(phtml)$ /index.php [NC,L]
```

```
RewriteCond %{REQUEST_FILENAME} -s [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -l [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -d
```

```
RewriteRule ^.*$ - [NC,L]
```

```
# The following rewrites all other queries to index.php. The  
# condition ensures that if you are using Apache aliases to do  
# mass virtual hosting, the base path will be prepended to  
# allow proper resolution of the index.php file; it will work  
# in non-aliased environments as well, providing a safe, one-size  
# fits all solution.
```

```
RewriteCond %{REQUEST_URI}::$1 ^(/.+)(.+)::\2$
```

```
RewriteRule ^(.*) - [E=BASE:%1]
```

```
RewriteRule ^(.*)$ %{ENV:BASE}index.php [NC,L]
```

```
#  
# associate .js with "text/javascript" type (if not present in mime.conf)  
#
```

```
AddType text/javascript .js
```

```
#  
# configure mod_expires  
# URL: http://httpd.apache.org/docs/2.2/mod/mod_expires.html  
# 10 days = 3600 * 24 * 10 = 864000  
# 30 days = 3600 * 24 * 10 = 2592000  
#
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive On
```

```
ExpiresDefault "access plus 5 seconds"
```

```
ExpiresByType image/x-icon "access plus 864000 seconds"
```

```
ExpiresByType image/jpeg "access plus 864000 seconds"
```

```
ExpiresByType image/gif "access plus 864000 seconds"
```

```
ExpiresByType image/png access plus 864000 seconds
ExpiresByType image/gif "access plus 864000 seconds"
ExpiresByType application/x-shockwave-flash "access plus 2592000 seconds"
ExpiresByType text/css "access plus 2592000 seconds"
ExpiresByType text/javascript "access plus 2592000 seconds"
ExpiresByType application/x-javascript "access plus 2592000 seconds"
# ExpiresByType text/html "access plus 10 seconds"
# ExpiresByType application/xhtml+xml "access plus 10 seconds"
</IfModule>

#
# configure mod_headers
# URL: http://httpd.apache.org/docs/2.2/mod/mod_headers.html
#
<IfModule mod_headers.c>
    <FilesMatch "\\.(ico|jpe?g|png|gif|swf)$">
        Header set Cache-Control "max-age=864000, public"
    </FilesMatch>
    <FilesMatch "\\.(css|js)$">
        Header set Cache-Control "max-age=2592000, public"
    </FilesMatch>
# <FilesMatch "(x?html?|php)$">
#     Header set Cache-Control "max-age=10, private, must-revalidate"
# </FilesMatch>
    Header unset ETag
    Header unset Last-Modified
</IfModule>
```