

```

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|tcl|otf|eot|woff|font. css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js

# Audio
AddType audio/ogg                    oga ogg
AddType audio/mp4                    m4a

# Video
AddType video/ogg                    ogv
AddType video/mp4                    mp4 m4v
AddType video/webm                   webm

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml               svg svgz
AddEncoding gzip                    svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf        ttf ttf-

```

```
AddType application/x-font-woff ttf ttc
AddType font/opentype otf
AddType application/x-font-woff woff
```

*# Assorted types*

```
AddType image/x-icon ico
AddType image/webp webp
AddType text/cache-manifest appcache manifest
AddType text/x-component htc
AddType application/xml rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpiinstall xpi
AddType application/octet-stream safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard vcf
```

```
# -----
# Gzip compression
# -----
```

```
<IfModule mod_deflate.c>
```

*# Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping/*

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
```

```
^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
```

```
RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

*# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:*

```
<IfModule filter_module>
```

```
FilterDeclare COMPRESS
```

```
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/html
```

```
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/css
```

```
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/plain
```

```
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/xml
```

```
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/x-component
```

```

FilterProvider COMPRESS DEFLATE resp=Content-Type $application/javascript
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/json
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/rss+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/atom+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/x-icon
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain COMPRESS
FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
    # Legacy versions of Apache
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
    AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml
application/atom+xml
    AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject
application/x-font-ttf font/opentype
</IfModule>

</IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.

<IfModule mod_rewrite.c>
    Options +FollowSymLinks -Indexes
    RewriteEngine On

    # If you installed Bonfire in a subfolder, you will need to
    # change the following line to match the subfolder you need.

```

```
# http://httpd.apache.org/docs/current/mod/mod_rewrite.html#rewritebase
RewriteBase /

#Removes access to the system folder by users.
#Additionally this will allow you to create a System.php controller,
#previously this would not have been possible.
#'system' can be replaced if you have renamed your system folder.
RewriteCond %{REQUEST_URI} ^bonfire/codeigniter.*
RewriteRule ^(.*)$ /index.php?/$1 [L]
</IfModule>

# Rewrite "www.example.com -> example.com"

<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

#Checks to see if the user is attempting to access a valid file,
#such as an image or css document, if this isn't true it sends the
#request to index.php

<IfModule mod_rewrite.c>
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(.*)$ index.php?/$1 [L]
</IfModule>

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .css .js .xml .json .rss .atom

# Block access to "hidden" directories whose names begin with a period. This
```

*# includes directories used by version control systems such as Subversion or Git.*

```
<IfModule mod_rewrite.c>
```

```
    RewriteCond %{SCRIPT_FILENAME} -d
```

```
    RewriteCond %{SCRIPT_FILENAME} -f
```

```
    RewriteRule "(^|/)\." - [F]
```

```
</IfModule>
```

```
<IfModule !mod_rewrite.c>
```

```
    # If we don't have mod_rewrite installed, all 404's
```

```
    # can be sent to index.php, and everything works as normal.
```

```
    # Submitted by: ElliotHaughin
```

```
    ErrorDocument 404 index.php
```

```
</IfModule>
```