



```
    header set Cache-Control max-age=604800, public
</FilesMatch>
<FilesMatch "\\. (js)$">
    Header set Cache-Control "max-age=216000, private"
</FilesMatch>
<FilesMatch "\\. (xml|txt)$">
    Header set Cache-Control "max-age=216000, public, must-revalidate"
</FilesMatch>
<FilesMatch "\\. (html|html php)$">
    Header set Cache-Control "max-age=1, private, must-revalidate"
</FilesMatch>
</IfModule>
```

*##-- Generation of Expires and Cache-Control HTTP headers*

```
<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault "access plus 1 seconds"
    ExpiresByType image/gif "access plus 2592000 seconds"
    ExpiresByType image/jpeg "access plus 2592000 seconds"
    ExpiresByType image/png "access plus 2592000 seconds"
    ExpiresByType text/html "access plus 1 seconds"
    ExpiresByType text/css "access plus 604800 seconds"
    ExpiresByType text/javascript "access plus 216000 seconds"
    ExpiresByType application/x-javascript "access plus 216000 seconds"
</IfModule>
```

*##-- Configure php\_flags if necessary*

*##-- BEGIN - use IfModule clause if PHP runs in CGI mode, otherwise just uncomment the lines with php\_flag..*

```
#<IfModule mod_php.c>
```

*##-- Warn when arguments are passed by reference at function call time (from PHP5 allow\_call\_time\_pass\_reference is deprecated)*

```
#php_flag allow_call_time_pass_reference on
```

*##-- Disable transparent sid support PHP-default is off (XTC Session only on first visit)*

```
#php_flag session.use_trans_sid off
```

*##-- set suhosin flags because of errors with attributes (for webhosters with suhosin hardening patch enabled)*

```
#php_flag suhosin.executor.safe_globals enabled
```

```

#php_value suhosin.post.max_array_depth 0
#php_value suhosin.post.max_array_index_length 0
#php_value suhosin.post.max_vars 0
#php_value suhosin.request.max_array_depth 0
#php_value suhosin.request.max_array_index_length 0
#php_value suhosin.request.max_vars 0

##-- set suhosin flags to have unencrypted session data, affecting "whos_online" &
"shopping cart" (for webhosters with suhosin hardening patch enabled)patch enabled
#php_value suhosin.session.encrypt Off
#php_value suhosin.session.cryptkey ''

##-- END - use IfModule clause if PHP runs in CGI mode, otherwise just uncomment the lines
with php_flag...
#</IfModule>

##-- Redirect error pages to Sitemap
##-- set the correct Path to ErrorDocument
ErrorDocument 400 /sitemap.html?error=400
ErrorDocument 401 /sitemap.html?error=401
ErrorDocument 402 /sitemap.html?error=402
ErrorDocument 403 /sitemap.html?error=403
ErrorDocument 404 /sitemap.html?error=404
ErrorDocument 500 /sitemap.html?error=500

##-----
##- SEO Shopstat Modul (Hartmut Koenig)
##-----
<IfModule mod_rewrite.c>
  ##-- Initialize and enable rewrite engine
  ##-- Documentation http://httpd.apache.org/docs/misc/rewriteguide.html
  RewriteEngine On

  ##-- EXAMPLE: If your shop is located at "http://www.yourdomain.com/shop",
  ##-- set the following line like e.g.: RewriteBase /shop/
  RewriteBase /

  ##-- Use canonical URLs
  ##-- redirect to www-domain, when www is missing and no subdomain given and not using an
  ssl-proxy
  ##-- HostEurope

```

```

#RewriteCond %{HTTP:X-Forwarded-Server} !^ssl\.webpack\.de$ [NC]
##-- 1und1
#RewriteCond %{HTTP:X-Forwarded-Server} !^ssl\.kundenserver\.de$ [NC]
##-- domainFACTORY
#RewriteCond %{HTTP:X-Forwarded-Server} !^ssl\sites\.de$ [NC]
##-- All-Inkl
#RewriteCond %{HTTP:X-Forwarded-Server} !^ssl-account\.com$ [NC]
##-- Strato
#RewriteCond %{HTTP:X-Forwarded-Server} !^www\.ssl-id\.de$ [NC]

#RewriteCond %{HTTP_HOST} !^www\.(\.)* [NC]
#RewriteCond %{HTTP_HOST} !^(.)*\.(\.)*\.(\.)* [NC]
#RewriteCond %{HTTP_HOST} !^localhost(\.)*$ [NC]
#RewriteRule ^(\.)* http://www.%{HTTP_HOST}/$1 [R=301,L]

##-- Sitemap
RewriteRule ^sitemap(\.)*\.html$ shop_content.php?coID=8 [QSA,L]

##-----
##-- When working with SEO-Urls you can decide, whether to use a colon ":" or a dash "-"
symbol
##-- (Windows Servers might have problems with colon as delimiter!)
##-- Change the delimiter symbol also in file "/inc/shopstat_functions.inc.php"
##-----

##-- Use colon delimiter ":" for SEO-URLS (default setting)
##-- Categories (::)
RewriteCond %{REQUEST_URI} (\.)*:::([\_0-9]+):([\_0-9]+)\.html$
RewriteRule (\.)*:::([\_0-9]+):([\_0-9]+)\.html$ index.php?cPath=$2&page=$3 [QSA,L]
RewriteCond %{REQUEST_URI} (\.)*:::([\_0-9]+)\.html$
RewriteRule (\.)*:::([\_0-9]+)\.html$ index.php?cPath=$2 [QSA,L]

##-- Products (:)
RewriteRule (\.)*:(\+)\.html$ product_info.php?products_id=$2 [QSA,L]

##-- Content (:_)
RewriteRule (\.)*:_:([\_0-9]+)\.html$ shop_content.php?coID=$2 [QSA,L]

##-- Manufacturers (::)
RewriteCond %{REQUEST_URI} (\.)*:::([\_0-9]+):([\_0-9]+)\.html$
RewriteRule (\.)*:::([\_0-9]+):([\_0-9]+)\.html$ index.php?manufacturers_id=$2&page=$3

```

[QSA, L]

```
RewriteCond %{REQUEST_URI} (.*):::([\_0-9]+\)\.html$
```

```
RewriteRule (.*):::([\_0-9]+\)\.html$ index.php?manufacturers_id=$2 [QSA, L]
```

```
##-- Use dash delimiter "-" for SEO-URLS
```

```
##-- Categories (---)
```

```
#RewriteCond %{REQUEST_URI} (.*)---([\_0-9]+)-([\_0-9]+\)\.html$
```

```
#RewriteRule (.*)---([\_0-9]+)-([\_0-9]+\)\.html$ index.php?cPath=$2&page=$3 [QSA, L]
```

```
#RewriteCond %{REQUEST_URI} (.*)---([\_0-9]+\)\.html$
```

```
#RewriteRule (.*)---([\_0-9]+\)\.html$ index.php?cPath=$2 [QSA, L]
```

```
##-- Products (--)
```

```
#RewriteRule (.*)--(, +)\.html$ product_info.php?products_id=$2 [QSA, L]
```

```
##-- Content (-_-)
```

```
#RewriteRule (.*)_-([\_0-9]+\)\.html$ shop_content.php?coID=$2 [QSA, L]
```

```
##-- Manufacturers (-, -)
```

```
#RewriteCond %{REQUEST_URI} (.*)-, -([\_0-9]+)-([\_0-9]+\)\.html$
```

```
#RewriteRule (.*)-, -([\_0-9]+)-([\_0-9]+\)\.html$ index.php?manufacturers_id=$2&page=$3
```

[QSA, L]

```
#RewriteCond %{REQUEST_URI} (.*)-, -([\_0-9]+\)\.html$
```

```
#RewriteRule (.*)-, -([\_0-9]+\)\.html$ index.php?manufacturers_id=$2 [QSA, L]
```

</IfModule>