

```
AddDefaultCharset UTF-8
```

```
# Turn on URL rewriting  
RewriteEngine On
```

```
AddDefaultCharset UTF-8
```

```
# Installation directory  
RewriteBase /
```

```
# Protect hidden files from being viewed
```

```
<Files . * >  
    Order Deny, Allow  
    Deny From All  
</Files>
```

```
# Protect application and system files from being viewed
```

```
RewriteRule ^(?: application| modules| system)\b. * index. php/$0 [L]
```

```
# Allow any files or directories that exist to be displayed directly
```

```
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d
```

```
# Rewrite all other URLs to index. php/URL
```

```
RewriteRule . * index. php/$0 [PT]
```

```
<IfModule mod_headers. c>
```

```
Header unset ETag
```

```
# clickjacking off
```

```
Header set X-Frame-Options: "sameorigin"
```

```
# MIME-sniffing
```

```
Header set X-Content-Type-Options: "nosniff"
```

```
# ...
```

```
Header unset X-Runtime
```

```
Header unset X-Powered-By
```

```
Header set X-XSS-Protection: "1; mode=block"
```

```
Header set X-WebKit-CSP: "default-src 'self' "
```

```
Header set X-Permitted-Cross-Domain-Policies: "master-only"
```

```
Header set strict-transport-security: "max-age=31536000; includeSubDomains"
```

```
</IfModule>
```