```
# Adds some security for the Apache server configuration for use with
# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf
through
# every folder on your server (which includes rather private places like CMS system
folders).
<IfModule mod_autoindex.c>
  Options -Indexes
</If Module>
<IfModule mod_rewrite.c>
# Block access to "hidden" directories whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
  RewriteCond %(SCRIPT_FILENAME) -d
  RewriteCond %(SCRIPT_FILENAME) -f
  RewriteRule "(^I/)\." - [F]
# Settings to hide index.php and ensure pretty urls
  RewriteEngine on
  # if a directory or a file exists, use it directly
  RewriteCond %(REQUEST_FILENAME) !-f
  RewriteCond %(REQUEST FILENAME) !-d
  # otherwise forward it to index.php
  RewriteRule . index.php
</If Module>
# Block access to backup and source files
# This files may be left by some text/html editors and
# pose a great security danger, when someone can access them
<FilesMatch "(\.(bak|config|sql|fla|psd|ini|log|sh|inc|swp|dist|gitignore)|~)$">
  Order allow, denu
  Deny from all
  Satisfy All
</FilesMatch>
# Increase cookie security
<IfModule php5_module>
  php_value session.cookie_httponly true
Z ZT & MALACIT AN
```