

ErrorDocument 404 /404.html

ErrorDocument 403 /403.html

#@__HCP_END__@#

Anything after the comment above is left alone

MIME-Types

<IfModule mod_mime.c>

Audio

AddType audio/mp4 m4a f4a f4b

AddType audio/ogg oga ogg

JavaScript

Normalize to standard type (it's sniffed in IE anyways):

<http://tools.ietf.org/html/rfc4329#section-7.2>

AddType application/javascript js

AddType application/json json

Video

AddType video/mp4 f4v f4p m4v mp4

AddType video/ogg ogv

AddType video/webm webm

AddType video/x-flv flv

Web fonts

AddType application/font-woff woff

AddType application/vnd.ms-fontobject eot

Browsers usually ignore the font MIME types and sniff the content,

however, Chrome shows a warning if other MIME types are used for the

following fonts.

AddType application/x-font-ttf ttc ttf

AddType font/opentype otf

Make SVGZ fonts work on iPad:

<https://twitter.com/FontSquirrel/status/14855840545>

AddType image/svg+xml svgz

AddEncoding gzip svgz

Done

```
# utner
AddType application/octet-stream          safariextz
AddType application/x-chrome-extension    crx
AddType application/x-opera-extension     oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall           xpi
AddType application/xml                   atom rdf rss xml
AddType image/webp                        webp
AddType image/x-icon                       cur
AddType text/cache-manifest               appcache manifest
AddType text/vtt                          vtt
AddType text/x-component                   htc
AddType text/x-vcard                       vcf
```

```
</IfModule>
```

```
# Force UTF-8
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
```

```
</IfModule>
```

```
# eTag
```

```
<IfModule mod_headers.c>
```

```
    Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
# HTTP Caching
```

```
<IfModule mod_expires.c>
```

```
    Header set cache-control: public
```

```
    ExpiresActive on
```

```
    ExpiresByType application/font-woff      "access plus 1 year"
```

```
    ExpiresByType application/vnd.ms-fontobject "access plus 1 year"
```

```
    ExpiresByType application/x-font-ttf     "access plus 1 year"
```

```
    ExpiresByType font/opentype              "access plus 1 year"
```

```
    ExpiresByType image/svg+xml             "access plus 1 year"
```

```
-----
```

```

ExpiresByType image/ico          "access plus 1 year"
ExpiresByType image/png          "access plus 1 week"
ExpiresByType image/jpeg        "access plus 1 week"

ExpiresByType text/html          "access plus 1 week"
ExpiresByType text/css           "access plus 1 week"
ExpiresByType application/javascript "access plus 1 week"
ExpiresByType application/xml    "access plus 1 week"
</IfModule>

# Compression
<IfModule mod_deflate.c>
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
      ^((gzip| deflate)\s*, ?\s*)+ [X"-](<4,13)$ HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>

  <IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
      application/javascript \
      application/json \
      application/rss+xml \
      application/vnd.ms-fontobject \
      application/x-font-ttf \
      application/font-woff \
      application/x-web-app-manifest+json \
      application/xhtml+xml \
      application/xml \
      font/opentype \
      image/svg+xml \
      image/x-icon \
      text/css \
      text/html \
      text/plain \
      text/x-component \
      text/xml
  </IfModule>
</IfModule>

```

