

```

# Rewrite www.example.com → example.com
<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+)$ [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]

    # This is added by me
    #RewriteCond %{HTTPS} !=on
    #RewriteCond %{SERVER_ADDR} !=127.0.0.1
    #RewriteCond %{SERVER_ADDR} !=::1
    #RewriteRule ^ https://%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
</IfModule>

# Block access to directories without a default document.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to hidden files and directories.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "^(.)/\." - [F]
</IfModule>

### Performance

# Compression
<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME types

```

```
# Compress all output labeled with one of the following mime-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
```

```
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/ld+json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

</IfModule>
```

```
</IfModule>
```

```
# Expires
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 week"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
```

```

# Favicon (cannot be renamed!) and cursor images
ExpiresByType image/x-icon "access plus 1 month"

# HTML components (HTCs)
ExpiresByType text/x-component "access plus 1 month"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 year"
ExpiresByType image/gif "access plus 1 year"
ExpiresByType image/jpeg "access plus 1 year"
ExpiresByType image/png "access plus 1 year"
ExpiresByType video/mp4 "access plus 1 year"
ExpiresByType video/ogg "access plus 1 year"
ExpiresByType video/webm "access plus 1 year"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"

```

```
</IfModule>
```

```

# Leverage proxy caching (Suggested by Google Chrome audit tool)
# Consider adding a "Cache-Control: public" header to the following resources...

```

```
<IfModule mod_headers.c>
  <FilesMatch "\.(jpg|jpeg|png)$">
    Header set Cache-Control "public"
  </FilesMatch>
</IfModule>
```

Lumen rewrites

```
<IfModule mod_rewrite.c>
  <IfModule mod_negotiation.c>
    Options -MultiViews
  </IfModule>
```

```
RewriteEngine On
```

Redirect Trailing Slashes...

```
RewriteRule ^(.*)/$ /$1 [L,R=301]
```

Handle Front Controller...

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteRule ^ index.php [L]
```

```
</IfModule>
```