

```
#

# Apache/PHP/Drupal settings:

#

# Protect files and directories from prying eyes.

<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xhtml|svn-
base)$|^(\code-style|.pl|Entries.*|Repository|Root|Tag|Template|all-
wcpops|entries|format)$">

    Order allow,deny

</FilesMatch>

# Don't show directory listings for URLs which map to a directory.

Options -Indexes

# Follow symbolic links in this directory.

Options +FollowSymLinks

# Make Drupal handle any 404 errors.

ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.

<Files favicon.ico>

    # There is no end quote below, for compatibility with Apache 1.3.

    ErrorDocument 404 "The requested file favicon.ico was not found.

</Files>

# Set the default handler.
```

DirectoryIndex index.php

*# Override PHP settings. More in sites/default/settings.php*

*# but the following cannot be changed at runtime.*

php\_value memory\_limit 256M

*# PHP 4, Apache 1.*

<IfModule mod\_php4.c>

php\_value magic\_quotes\_gpc 0

php\_value register\_globals 0

php\_value session.auto\_start 0

php\_value mbstring.http\_input pass

php\_value mbstring.http\_output pass

php\_value mbstring.encoding\_translation 0

</IfModule>

*# PHP 4, Apache 2.*

<IfModule sapi\_apache2.c>

php\_value magic\_quotes\_gpc 0

php\_value register\_globals 0

php\_value session.auto\_start 0

php\_value mbstring.http\_input pass

php\_value mbstring.http\_output pass

.....

```
php_value mbstring.encoding_translation 0

</IfModule>

# PHP 5, Apache 1 and 2.

<IfModule mod_php5.c>

    php_value magic_quotes_gpc 0

    php_value register_globals 0

    php_value session.auto_start 0

    php_value mbstring.http_input pass

    php_value mbstring.http_output pass

    php_value mbstring.encoding_translation 0

</IfModule>

# Requires mod_expires to be enabled.

<IfModule mod_expires.c>

    # Enable expirations.

    ExpiresActive On

    # Cache all files for 2 weeks after access (A).

    ExpiresDefault A1209600

<FilesMatch \.php$>

    # Do not allow PHP scripts to be cached unless they explicitly send cache

    # headers themselves. Otherwise all scripts would have to overwrite the

    # headers set by mod_expires if they want another caching behavior. This may
```

```
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# If your site can be accessed both with and without the 'www.' prefix, you  
# can use one of the following settings to redirect users to your preferred  
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
```

```
#
```

```
# To redirect all users to access the site WITH the 'www.' prefix,  
# (http://example.com/... will be redirected to http://www.example.com/...)
```

```
# adapt and uncomment the following:
```

```
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
```

```
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
```

```
#
```

```
# To redirect all users to access the site WITHOUT the 'www.' prefix,  
# (http://www.example.com/... will be redirected to http://example.com/...)
```

*# uncomment and adapt the following:*

*# RewriteCond %{HTTP\_HOST} ^www\..example\..com\$ [NC]*

*# RewriteRule ^(.\*)\$ http://example.com/\$1 [L,R=301]*

*# Modify the RewriteBase if you are using Drupal in a subdirectory or in a*

*# VirtualDocumentRoot and the rewrite rules are not working properly.*

*# For example if your site is at http://example.com/drupal uncomment and*

*# modify the following line:*

*# RewriteBase /comunidad*

*#*

*# If your site is running in a VirtualDocumentRoot at http://example.com/,*

*# uncomment the following line:*

*# RewriteBase /*

php\_value upload\_max\_filesize 10M

php\_value post\_max\_size 10M

*# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.*

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_FILENAME} !-d

RewriteCond %{REQUEST\_URI} !=/favicon.ico

RewriteRule ^(.\*)\$ index.php?q=\$1 [L,QSA]

</IfModule>

*# \$Id\$*

