```apache
AddType application/x-web-app-manifest+json .webapp
RewriteEngine On

# Some hosts may require you to use the `RewriteBase` directive.
# If you need to use the `RewriteBase` directive, it should be the
# absolute physical path to the directory that contains this htaccess file.
#
# RewriteBase /

RewriteRule ^server-status - [L]
RewriteRule ^api - [L]

RewriteCond %{REQUEST_FILENAME} -f
RewriteRule .* - [L]

# mobile detection, source http://detectmobilebrowsers.com/
RewriteCond %{HTTP_USER_AGENT} (android| bb\d+| meego).+mobile| avantgo| bada\/| blackberry| blaze
| phone| p(ixi| re)\/| plucker| pocket| psp| series(4| 6)0| symbian| treo| up\.(browser| link)| vodafone|
RewriteCond %{HTTP_USER_AGENT} ^(1207| 6310| 6590| 3gso| 4thp| 50[1-6]i| 770s| 802s| a\ wa| abac| ac(e
)| avan| be(ck| ll| nq)| bi(lb| rd)| bl(ac| az)| br(e| v)w| bumb| bw\-(n| u)| c55\/| capi| ccwa| cdm\-| cell| c
7|0| os| wa| ze)| fetc| fly(\-| _)| g1\ u| g560| gene| gf\-5| g\-mo| go(\. w| od)| gr(ad| un)| haie| hcit| hd\-
|\/)| ibro| idea| ig01| ikom| im1k| inno| ipaq| iris| ja(t| v)a| jbro| jemu| jigs| kddi| keji| kgt(\ |\/)| kl
cr| me(rc| ri)| mi(o8| oa| ts)| mmef| mo(01| 02| bi| de| do| t(\-|\ | o| v)| zz)| mt(50| p1| v\ )| mwbp| mywa| nl
| on| tf| wf| wg| wt)| nok(6| i)| nzph| o2im| op(ti| wv)| oran| owg1| p800| pan(a| d| t)| pdxg| pg(13| \-([1-8]|
)| qtek| r380| r600| raks| rim9| ro(ve| zo)| s55\/| sa(ge| ma| mm| ms| ny| va)| sc(01| h\-| oo| p\-)| sdk\/| se(
)| sy(01| mb)| t2(18| 50)| t6(00| 10| 18)| ta(gt| lk)| tcl\-| tdg\-| tel(i| m)| tim\-| t\-mo| to(pl| sh)| ts(7
|\ )| webc| whit| wi(g\ | nc| nw)| wmlb| wonu| x700| yas\-| your| zeto| zte\-) [NC]
RewriteRule ^ index.php [QSA,L,E=mobile:1]

# RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^ index.php [QSA,L]
#RewriteRule ^about.php index.php?about=1 [QSA,L]
```