

RewriteEngine on

RewriteRule ^(.+)\.[0-9]+\.(js|css)\$ \$1.\$2 [L]

RewriteCond \$1 !^(index\.php|apple-touch-icon-precomposed\.png|apple-touch-
icon\.png|direct|direct\.php|images|assets|robots\.txt|favicon\.ico|favicon\.gif|favicon\.pr

RewriteRule ^(.*)\$./index.php?/\$1 [L]

#####

<IfModule mod_headers.c>

Header set X-UA-Compatible "IE=Edge,chrome=1"

*# mod_headers can't match by content-type, but we don't want to send this header on *ever!*

<FilesMatch "\.(js|css|gif|png|jpe?

gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svgl|svgz|eotl|ttfl|otfl|woffl|icol|webpl|appcachel|manifestl
>

Header unset X-UA-Compatible

</FilesMatch>

</IfModule>

<IfModule mod_setenvif.c>

<IfModule mod_headers.c>

mod_headers, y u no match by Content-Type?!

<FilesMatch "\.(gif|png|jpe?gl|svgl|svgz|icol|webp)\$">

SetEnvIf Origin ":" IS_CORS

Header set Access-Control-Allow-Origin "*" env=IS_CORS

</FilesMatch>

</IfModule>

</IfModule>

<IfModule mod_headers.c>

<FilesMatch "\.(ttfl|ttcl|otfl|eotl|woffl|font.css)\$">

Header set Access-Control-Allow-Origin "*"

</FilesMatch>

</IfModule>

Proper MIME type for all files

Trailing slash

```

# javascript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Audio
AddType audio/ogg                   oga ogg
AddType audio/mp4                   m4a f4a f4b

# Video
AddType video/ogg                   ogv
AddType video/mp4                   mp4 m4v f4v f4p
AddType video/webm                  webm
AddType video/x-flv                 flv

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml              svg svgz
AddEncoding gzip                   svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf       ttf ttc
AddType font/opentype               otf
AddType application/x-font-woff      woff

# Assorted types
AddType image/x-icon                 ico
AddType image/webp                   webp
AddType text/cache-manifest          appcache manifest
AddType text/x-component             htc
AddType application/xml              rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpi-install    xpi
AddType application/octet-stream     safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard                 vcf
AddType application/x-shockwave-flash swf
AddType application/javascript       js

```

```

AddType text/vtt                                vtt

<IfModule mod_deflate.c>

    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip deflate)\
HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \
            application/rss+xml \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            application/xhtml+xml \
            application/xml \
            font/opentype \
            image/svg+xml \
            image/x-icon \
            text/css \
            text/html \
            text/plain \
            text/x-component \
            text/xml

    </IfModule>

</IfModule>

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault                                "access plus 1 month"

    # cache, apcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest            "access plus 0 seconds"

```

```
# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>
```

```
# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

<filesMatch "\.(jpg|jpeg|png|gif|swf|webm|mp4|ogv)$">
Header set Cache-Control "max-age=604800, public"
</filesMatch>
```

```
#####
```

```
Options All -Indexes
```

```
Header unset ETag
```

```
FileETag None
```