

```
<IfModule mod_rewrite.c>
  Options +FollowSymlinks
  # Options +SymLinksIfOwnerMatch
  RewriteEngine On
  # RewriteBase /

RewriteCond %{REQUEST_URI} /+([^\.]+)$
RewriteRule ^(.+([^/])$ %{REQUEST_URI}/ [R=301,L]

RewriteCond %{SCRIPT_FILENAME} !-d
RewriteCond %{SCRIPT_FILENAME} !-f

RewriteRule ^about$ ./index.php [L]
RewriteRule ^about/$ ./index.php [L]

RewriteRule ^work$ ./index.php [L]
RewriteRule ^work/$ ./index.php [L]

RewriteRule ^forney-tx-web-development$ ./index.php [L]
RewriteRule ^forney-tx-web-development/$ ./index.php [L]

RewriteRule ^dallas-tx-web-development$ ./index.php [L]
RewriteRule ^dallas-tx-web-development/$ ./index.php [L]

RewriteRule ^rockwall-tx-web-development$ ./index.php [L]
RewriteRule ^rockwall-tx-web-development/$ ./index.php [L]

RewriteRule ^heath-tx-web-development$ ./index.php [L]
RewriteRule ^heath-tx-web-development/$ ./index.php [L]

RewriteRule ^contact$ ./index.php [L]
RewriteRule ^contact/$ ./index.php [L]

RewriteRule ^success$ ./index.php [L]
RewriteRule ^success/$ ./index.php [L]

RewriteRule ^blog$ ./index.php [L]
RewriteRule ^blog/$ ./index.php [L]

# RewriteRule ^404$ ./index.php?error=404 [L]
# RewriteRule ^404$ /index.php?error=404 [L]
```

```
# RewriteRule 404/$ ./index.php?error=404 [L]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(.*)$ index.php/blog/?filename=$1 [NC,QSA,L]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(.*)$ index.php/work/?workname=$1 [NC,QSA,L]

</IfModule>

# BEGIN GZIP
<ifmodule mod_deflate.c>
AddOutputFilterByType DEFLATE text/text text/html text/plain text/xml text/css
application/x-javascript application/javascript
</ifmodule>
# END GZIP

# Browser Caching
ExpiresActive On
ExpiresByType image/gif A2592000
ExpiresByType image/jpeg A2592000
ExpiresByType image/jpg A2592000
ExpiresByType image/png A2592000
ExpiresByType image/x-icon A2592000
ExpiresByType text/css A86400
ExpiresByType text/javascript A86400
ExpiresByType application/x-shockwave-flash A2592000
#
<FilesMatch "\.(gif|jpe?g|png|ico|css|js|swf)$">
Header set Cache-Control "public"
</FilesMatch>
# END Browser Caching

# #####
# # ERRORS #
# #####

# -----
# | 404 error prevention for non-existing redirected folders |
# -----

" </pre></div>
```

```
# Prevent Apache from returning a 404 error for a rewrite if a directory
# with the same name does not exist.
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews
# http://www.webmasterworld.com/apache/3808792.htm
```

## Options -MultiViews

```
# -----
# | Custom error messages / pages |
# -----

# You can customize what Apache returns to the client in case of an error (see
# http://httpd.apache.org/docs/current/mod/core.html#errordocument), e.g.:
```

## ErrorDocument 404 /404.php

```
# #####
# # INTERNET EXPLORER #
# #####

# -----
# | Better website experience |
# -----

# Force IE to render pages in the highest available mode in the various
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.
```

```
<IfModule mod_headers.c>
```

```
Header set X-UA-Compatible "IE=edge"
```

```
# `mod_headers` can't match based on the content-type, however, we only
# want to send this header for HTML pages and not for the other resources
```

```
<FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?"
```

```
g|js|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|otf|pdf|png|safariextz|svg?"
```

```
|ttf|vcf|webapp|webm|webp|woff|xml|xpi)$">
```

```
Header unset X-UA-Compatible
```

```
</FilesMatch>
```

```
</IfModule>
```