

```
Options +FollowSymLinks
```

```
RewriteEngine On
```

```
RewriteCond %{SCRIPT_FILENAME} !-d
```

```
RewriteCond %{SCRIPT_FILENAME} !-f
```

```
RewriteRule ^store$ ./store.php
```

```
RewriteRule ^store/$ ./store.php
```

```
RewriteRule ^about$ ./about.php
```

```
RewriteRule ^about/$ ./about.php
```

```
RewriteRule ^contact$ ./contact.php
```

```
RewriteRule ^contact/$ ./contact.php
```

```
RewriteRule ^contactthanks$ ./contactthanks.php
```

```
RewriteRule ^contactthanks/$ ./contactthanks.php
```

```
# BEGIN GZIP
```

```
<ifmodule mod_deflate.c>
```

```
AddOutputFilterByType DEFLATE text/text text/html text/plain text/xml text/css  
application/x-javascript application/javascript
```

```
</ifmodule>
```

```
# END GZIP
```

```
# Browser Caching
```

```
ExpiresActive On
```

```
ExpiresByType image/gif A2592000
```

```
ExpiresByType image/jpeg A2592000
```

```
ExpiresByType image/jpg A2592000
```

```
ExpiresByType image/png A2592000
```

```
ExpiresByType image/x-icon A2592000
```

```
ExpiresByType text/css A86400
```

```
ExpiresByType text/javascript A86400
```

```
ExpiresByType application/x-shockwave-flash A2592000
```

```
#
```

```
<FilesMatch "\.(gif|jpe?g|png|ico|css|js|swf)$">
```

```
Header set Cache-Control "public"
```

```
</FilesMatch>
```

```
# END Browser Caching
```

```
# #####
# # ERRORS #
# #####

# -----
# | 404 error prevention for non-existing redirected folders |
# -----

# Prevent Apache from returning a 404 error for a rewrite if a directory
# with the same name does not exist.
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews
# http://www.webmasterworld.com/apache/3808792.htm
```

### Options -MultiViews

```
# -----
# | Custom error messages / pages |
# -----

# You can customize what Apache returns to the client in case of an error (see
# http://httpd.apache.org/docs/current/mod/core.html#errordocument), e.g.:
```

### ErrorDocument 404 /404.php

```
# #####
# # INTERNET EXPLORER #
# #####

# -----
# | Better website experience |
# -----

# Force IE to render pages in the highest available mode in the various
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.
```

```
<IfModule mod_headers.c>
```

```
Header set X-UA-Compatible "IE=edge"
```

```
# `mod_headers` can't match based on the content-type, however, we only
# want to send this header for HTML pages and not for the other resources
<FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?
```

```
gl jsl m4al m4vl manifestl mp4l oexl ogal oggl ogvl otfl pdfl pngl safarixtzi svgz?  
| ttf| vcf| webappl webml webpl woffl xml| xpi)">  
    Header unset X-UA-Compatible  
    </FilesMatch>  
</IfModule>
```