

Options -MultiViews

RewriteEngine On

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule ^(.+)\$ index.php?url=\$1 [QSA,L]

BEGIN GZIP

<ifmodule mod_deflate.c>

AddOutputFilterByType DEFLATE text/text text/html text/plain text/xml text/css
application/x-javascript application/javascript

</ifmodule>

END GZIP

Browser Caching

ExpiresActive On

ExpiresDefault "access plus 1 month"

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType image/jpg "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType image/x-icon "access plus 1 month"

ExpiresByType text/css "access plus 7 days"

ExpiresByType text/javascript "access plus 7 days"

###

<FilesMatch "\.(gif|jpe?g|png|ico|css|js|swf)\$">

Header set Cache-Control "public"

</FilesMatch>

END Browser Caching

#####

ERRORS

#####

-----

| 404 error prevention for non-existing redirected folders |

-----

Prevent Apache from returning a 404 error for a rewrite if a directory

with the same document root

```
# with the same name does not exist.  
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews  
# http://www.webmasterworld.com/apache/3808792.htm
```

Options -MultiViews

```
# -----  
# | Custom error messages / pages |  
# -----
```

```
# You can customize what Apache returns to the client in case of an error (see  
# http://httpd.apache.org/docs/current/mod/core.html#errordocument), e.g.:
```

ErrorDocument 404 /404.php

```
# #####  
# # INTERNET EXPLORER #  
# #####
```

```
# -----  
# | Better website experience |  
# -----
```

```
# Force IE to render pages in the highest available mode in the various  
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.
```

```
<IfModule mod_headers.c>
```

```
Header set X-UA-Compatible "IE=edge"
```

```
# `mod_headers` can't match based on the content-type, however, we only  
# want to send this header for HTML pages and not for the other resources
```

```
<FilesMatch "\.(appcache|crx|css|eot|gif|htc|ico|jpe?
```

```
g|js|m4a|m4v|manifest|mp4|oex|og|ogg|ogv|otf|pdf|png|safariextz|svg?
```

```
ttf|vcf|webapp|webm|webp|woff|xml|xpi)$">
```

```
Header unset X-UA-Compatible
```

```
</FilesMatch>
```

```
</IfModule>
```