

```
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xmp|svn-
base)$|^(\code-style\.|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found."
</Files>

# Set the default handler.
DirectoryIndex index.php

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

<FilesMatch \.php$>
    # Do not allow PHP scripts to be cached unless they explicitly send cache
    # headers themselves. Otherwise all scripts would have to override the
```

```
# headers themselves, otherwise all scripts would have to overwrite the
# headers set by mod_expires if they want another caching behavior. This may
# fail if an error occurs early in the bootstrap process, and it may cause
# problems if a non-Drupal PHP file is installed in a subdirectory.
ExpiresActive Off
</FilesMatch>
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on

  ### BOOST START ###
  AddDefaultCharset utf-8
  <FilesMatch "(\\.html|\\.html\\.gz)$">
    <IfModule mod_headers.c>
      Header set Expires "Sun, 19 Nov 1978 05:00:00 GMT"
      Header set Cache-Control "no-store, no-cache, must-revalidate, post-check=0, pre-
check=0"
    </IfModule>
  </FilesMatch>
  <IfModule mod_mime.c>
    AddCharset utf-8 .html
    AddCharset utf-8 .css
    AddCharset utf-8 .js
    AddEncoding gzip .gz
  </IfModule>
  <FilesMatch "(\\.html|\\.html\\.gz)$">
    ForceType text/html
  </FilesMatch>
  <FilesMatch "(\\.js|\\.js\\.gz)$">
    ForceType text/javascript
  </FilesMatch>
  <FilesMatch "(\\.css|\\.css\\.gz)$">
    ForceType text/css
  </FilesMatch>

  ### BOOST END ###

# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^([^.]+)$ /index.php?q=$1 [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.5 2010/02/02 07:25:22 dries Exp $
```