

```

#
# @copyright Copyright 2003-2013 Zen Cart Development Team
# @license http://www.zen-cart.com/license/2_0.txt GNU Public License V2.0
# @version $Id: .htaccess 18695 2011-05-04 05:24:19Z drbyte $
#

## the following line is needed to allow Download-By-Redirect to work
## If your web host doesn't allow the FollowSymLinks option, consider replacing
+FollowSymLinks with +SymLinksIfOwnerMatch

Options +FollowSymLinks

#
# This is used with Apache WebServers
#
# The following blocks direct HTTP requests to all filetypes in this directory
recursively, except certain approved exceptions
# It also prevents the ability of any scripts to run. No type of script, be it PHP, PERL
or whatever, can normally be executed if ExecCGI is disabled.
# Will also prevent people from seeing what is in the dir. and any sub-directories
#
# For this to work, you must include either 'All' or at least: 'Limit' and 'Indexes'
parameters to the AllowOverride configuration in your apache/conf/httpd.conf file.
# Additionally, if you want the added protection offered by the OPTIONS directive below,
you'll need to add 'Options' to the AllowOverride list, if 'All' is not specified.
# Example:
#<Directory "/usr/local/apache/htdocs">
# AllowOverride Limit Options Indexes
#</Directory>
#####

# deny *everything*
<FilesMatch ".*">
  <IfModule mod_authz_core.c>
    Require all denied
  </IfModule>
  <IfModule !mod_authz_core.c>
    Order Allow,Deny
    Deny from all
  </IfModule>
</FilesMatch>

```

```
</FilesMatch>
```

```
# but now allow just *certain* necessary files:
```

```
<FilesMatch "(?i).*\.(zip|gzip|pdf|mp3|swf|wm|wml|wav|epub|ogg|webm|m4v|m4a)$">
```

```
  <IfModule mod_authz_core.c>
```

```
    Require all granted
```

```
  </IfModule>
```

```
  <IfModule !mod_authz_core.c>
```

```
    Order Allow,Deny
```

```
    Allow from all
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
<IfModule mod_headers.c>
```

```
  <FilesMatch "(?i).*\.(zip|gzip|pdf|mp3|swf|wm|wml|wav|epub|ogg|m4v|m4a)$">
```

```
    # tell all downloads to automatically be treated as "save as" instead of launching in  
    an application directly
```

```
    # ALERT: ForceType requires Apache2 or later. If using older version of Apache, it  
    will need mod_mime installed. Or just comment out the ForceType line below
```

```
    # (to disable, just comment the next 2 lines by adding a '#' at the beginning of  
    each):
```

```
    ForceType application/octet-stream
```

```
    Header set Content-Disposition attachment
```

```
  </FilesMatch>
```

```
</IfModule>
```

```
IndexIgnore /*
```

```
## NOTE: If you want even greater security to prevent hackers from running scripts in this  
folder, uncomment the following line (if your hosting company will allow you to use  
OPTIONS):
```

```
# OPTIONS -Indexes -ExecCGI
```