

```

# -----
# | Custom error messages/pages |
# -----

# Customize what Apache returns to the client in case of an error.
# https://httpd.apache.org/docs/current/mod/core.html#errordocument

#ErrorDocument 404 /404.html

# -----
# | File access |
# -----

# Block access to directories without a default document.

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----
# | Expires headers |
# -----

# Serve resources with far-future expires headers.
#
# (!) If you don't control versioning with filename-based
# cache busting, you should consider lowering the cache times
# to something like one week.
#
# https://httpd.apache.org/docs/current/mod/mod\_expires.html

<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

# CSS
    ExpiresByType text/css "access plus 1 week"

# Data interchange
    ExpiresByType application/javascript "access plus 1 hour"

```


Embedded OpenType (EOT)

ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"

OpenType

ExpiresByType font/opentype "access plus 1 month"

TrueType

ExpiresByType application/x-font-ttf "access plus 1 month"

Web Open Font Format (WOFF) 1.0

ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"

Web Open Font Format (WOFF) 2.0

ExpiresByType application/font-woff2 "access plus 1 month"

Other

ExpiresByType text/x-cross-domain-policy "access plus 1 week"

</IfModule>