

```
#####
## uncomment the line below to enable developer mode

# SetEnv MAGE_MODE developer

#####
## uncomment these lines for CGI mode
## make sure to specify the correct cgi php binary file name
## it might be /cgi-bin/php-cgi

# Action php5-cgi /cgi-bin/php5-cgi
# AddHandler php5-cgi .php

#####
## GoDaddy specific options

# Options -MultiViews

## you might also need to add this line to php.ini
## cgi.fix_pathinfo = 1
## if it still doesn't work, rename php.ini to php5.ini

#####
## this line is specific for 1and1 hosting

#AddType x-mapp-php5 .php
#AddHandler x-mapp-php5 .php

#####
## default index file

DirectoryIndex index.php

<IfModule mod_php5.c>

#####
## adjust memory limit

php_value memory_limit 256M
php_value max_execution_time 18000
```

```
#####
```

```
## disable automatic session start  
## before autoload was initialized
```

```
php_flag session.auto_start off
```

```
#####
```

```
## enable resulting html compression
```

```
#php_flag zlib.output_compression on
```

```
#####
```

```
# disable user agent verification to not break multiple image upload
```

```
php_flag suhosin.session.cryptua off
```

```
</IfModule>
```

```
<IfModule mod_php7.c>
```

```
#####
```

```
## adjust memory limit
```

```
php_value memory_limit 256M  
php_value max_execution_time 18000
```

```
#####
```

```
## disable automatic session start  
## before autoload was initialized
```

```
php_flag session.auto_start off
```

```
#####
```

```
## enable resulting html compression
```

```
#php_flag zlib.output_compression on
```

```
#####
```

```
# disable user agent verification to not break multiple image upload
```

```
php_flag suhosin.session.cryptua off
```

```
</IfModule>
```

```
<IfModule mod_security.c>
```

```
#####
```

```
# disable POST processing to not break multiple image upload
```

```
    SecFilterEngine Off
```

```
    SecFilterScanPOST Off
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
#####
```

```
## enable apache served files compression
```

```
## http://developer.yahoo.com/performance/rules.html#gzip
```

```
# Insert filter on all content
```

```
###SetOutputFilter DEFLATE
```

```
# Insert filter on selected content types only
```

```
#AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript
```

```
# Netscape 4.x has some problems...
```

```
#BrowserMatch ^Mozilla/4 gzip-only-text/html
```

```
# Netscape 4.06-4.08 have some more problems
```

```
#BrowserMatch ^Mozilla/4\.[0678] no-gzip
```

```
# MSIE masquerades as Netscape, but it is fine
```

```
#BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
```

```
# Don't compress images
```

```
#SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip dont-vary
```

```
# Make sure proxies don't deliver the wrong content
```

```
#Header append Vary User-Agent env=!dont-vary
```

```
</IfModule>
```

```
<IfModule mod_ssl.c>
```

```
#####
## make HTTPS env vars available for CGI mode

    SSLOptions StdEnvVars

</IfModule>

<IfModule mod_rewrite.c>

#####
## enable rewrites

    Options +FollowSymLinks
    RewriteEngine on

#####
## you can put here your magento root folder
## path relative to web root

    #RewriteBase /magento/

#####
## workaround for HTTP authorization
## in CGI environment

    RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

#####
## TRACE and TRACK HTTP methods disabled to prevent XSS attacks

    RewriteCond %{REQUEST_METHOD} ^TRAC[EK]
    RewriteRule .* - [L,R=405]

#####
## never rewrite for existing files, directories and links

    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_FILENAME} !-l
```

```
#####
## rewrite everything else to index.php

    RewriteRule .* index.php [L]

</IfModule>

#####
## Prevent character encoding issues from server overrides
## If you still have problems, use the second line instead

    AddDefaultCharset Off
    #AddDefaultCharset UTF-8

<IfModule mod_expires.c>

#####
## Add default Expires header
## http://developer.yahoo.com/performance/rules.html#expires

    ExpiresDefault "access plus 1 year"
    ExpiresByType text/html A0
    ExpiresByType text/plain A0

</IfModule>

#####
## Deny access to release notes to prevent disclosure of the installed Magento version

    <Files RELEASE_NOTES.txt>
        order allow,deny
        deny from all
    </Files>

#####
## If running in cluster environment, uncomment this
## http://developer.yahoo.com/performance/rules.html#etags

    #FileETag none

#####
```

```
## Deny access to cron.php
<Files cron.php>
    order allow,deny
    deny from all
</Files>

<IfModule mod_headers.c>
    #####
    ## prevent clickjacking
    Header set X-Frame-Options SAMEORIGIN
</IfModule>
```