

```

<IfModule mod_mime.c>
    # Force UTF-8 for certain file formats.
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

<IfModule mod_rewrite.c>
    # Rewrite laravel-tricks.com to www.laravel-tricks.com
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} !^www\. .+$ [NC]
    RewriteCond %{HTTP_HOST} !=localhost [NC]
    RewriteCond %{HTTP_HOST} !=127.0.0.1
    RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
</IfModule>

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

<IfModule mod_headers.c>
    # Better content-type protection.
    Header set X-Content-Type-Options "nosniff"
</IfModule>

<IfModule mod_rewrite.c>
    # Forbid access to hidden files / folders.
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]

    # Better cachebusting (e.g. bootstrap.1.css instead of bootstrap.css?v1)
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteRule ^(\.+)\.(.+)\.(jst|css|png|jpg|gif)$ $1.$3 [L]

<IfModule mod_negotiation.c>
    Options -MultiViews
</IfModule>

RewriteEngine On

# Rewrite trailing slashes
RewriteRule ^(.+)$ /$1/ [R=301,L]

```

```

RewriteRule \.*/$ /$1 [L,R=301]

# Handle front controller
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^ index.php [L]
</IfModule>

<IfModule mod_deflate.c>

# Force compression for mangled headers.
# http://developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping
<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$
^((gzip|deflate)\s*,?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
        RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        . . . . .

```

text/xml

</IfModule>

</IfModule>

<IfModule mod_headers.c>

Header unset ETag

</IfModule>

FileETag None

<IfModule mod_expires.c>

ExpiresActive on

ExpiresDefault "access plus 1 month"

CSS

ExpiresByType text/css "access plus 1 year"

Data interchange

ExpiresByType application/json "access plus 0 seconds"

ExpiresByType application/xml "access plus 0 seconds"

ExpiresByType text/xml "access plus 0 seconds"

Favicon (cannot be renamed!) and cursor images

ExpiresByType image/x-icon "access plus 1 week"

HTML components (HTCs)

ExpiresByType text/x-component "access plus 1 month"

HTML

ExpiresByType text/html "access plus 0 seconds"

JavaScript

ExpiresByType application/javascript "access plus 1 year"

Manifest files

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"

ExpiresByType text/cache-manifest "access plus 0 seconds"

Media

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

</IfModule>