```apache
# Do not let apache guess the URL intentions, either it is correct or not.
Options -MultiViews

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Set HTTPS environment variable if we came in over secure channel.
SetEnvIf x-forwarded-proto https HTTPS=on

#keep prying eyes out of our config files
<files *.ini>
  order allow,deny
  deny from all
</files>

#keep prying eyes out of our pw files
<files *.pw>
  order allow,deny
  deny from all
</files>

#disallow any *.php file except index*.php
<FilesMatch "\.php$">
    Order Allow,Deny
    Deny from all
</FilesMatch>
<FilesMatch "index.*\.php$">
    Order Allow,Deny
    Allow from all
</FilesMatch>

#phpBitsTheater framework redirection
<IfModule mod_rewrite.c>
  RewriteEngine On
#needed for HTTP Basic authorization
  RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^(.*)$ index.php?url=$1 [PT,QSA,L]
</IfModule>
```

```
#Please consider moving the contents of this file into
#your webserver's httpd.conf like so:
#
#     <Directory /www/this/folders/path>
#     RewriteCond ...
#     </Directory>
#
#The resulting performance & security gains may be worth it.
```