

```
## Production .htaccess file

<FilesMatch ".(php|html|htm|js|css)$">
    FileETag None
    <ifModule mod_headers.c>
        Header unset ETag
        Header set Cache-Control "max-age=0, no-cache, no-store, must-revalidate"
        Header set Pragma "no-cache"
        Header set Expires "Wed, 11 Jan 1984 05:00:00 GMT"
    </ifModule>
</FilesMatch>

RewriteEngine On
RewriteBase /
# The following rule tells Apache that if the requested filename
# exists, simply serve it.
RewriteCond %{REQUEST_FILENAME} -s [OR]
RewriteCond %{REQUEST_FILENAME} -l [OR]
RewriteCond %{REQUEST_FILENAME} -d
RewriteRule ^.*$ - [NC,L]
# The following rewrites all other queries to index.php. The
# condition ensures that if you are using Apache aliases to do
# mass virtual hosting, the base path will be prepended to
# allow proper resolution of the index.php file; it will work
# in non-aliased environments as well, providing a safe, one-size
# fits all solution.
RewriteCond %{REQUEST_URI}::$1 ^(/.+/+.+)/\2$ 
RewriteRule ^(.*) - [E=BASE: %1]
RewriteRule ^(.*)$ %{ENV: BASE}index.php [NC,L]
```