

```
Header set X-UA-Compatible "IE=edge"
```

```
Options +FollowSymLinks
```

```
RewriteEngine On
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule . index.php [L]
```

```
<IfModule mod_deflate.c>
```

```
# Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping/
```

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
```

```
^(|(gzip|deflate)\s*,?\s*)+([X^~]{4,13})$ HAVE_Accept-Encoding
```

```
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-font-ttf ttf ttc
```

```
AddType font/opentype otf
```

```
AddType application/x-font-woff woff
```

```
AddType image/svg+xml svg svgz
```

```
</IfModule>
```

```
# Compress all output labeled with one of the following MIME-types
```

```
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
```

```
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
```

```
# `AddOutputFilterByType` is still in the core directives)
```

```
#<IfModule mod_filter.c>
```

```
AddOutputFilterByType DEFLATE application/atom+xml \
```

```
application/javascript \
```

```
application/x-javascript \
```

```
application/json \
```

```
application/rss+xml \
```

```
application/vnd.ms-fontobject \
```

```
application/x-font-ttf \
```

```
application/x-font-woff \
```

```
application/xhtml+xml \
```

```
application/xhtml+xml \
application/xml \
font/opentype \
image/svg+xml \
image/x-icon \
text/css \
text/html \
text/javascript \
text/plain \
text/x-component \
text/xml
```

```
#</IfModule>
```

```
</IfModule>
```