

```
# Apache Server Configs v2.2.0 | MIT License
# https://github.com/h5bp/server-configs-apache

# -----
# CORS-enabled images
# -----

# Send the CORS header for images when browsers request it.
# https://developer.mozilla.org/en-US/docs/HTML/CORS_Enabled_Image
# http://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# http://hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    <FilesMatch "\.(curl|gif|ico|jpe?g|png|svgz?|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access to web fonts from all domains.

<IfModule mod_headers.c>
  <FilesMatch "\.(eot|otf|tt[cf]|woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Internet Explorer
# -----

# Force IE to render pages in the highest available mode in the various
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.
```

```

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge"
  # 'mod_headers' can't match based on the content-type, however, we only
  # want to send this header for HTML pages and not for the other resources
  <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|icol|jpe?
  gl|jst|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogvl|opus|otf|pdf|png|safariextz|svgz?
  |ttf|vcf|webapp|webml|webpl|woff|xml|xpi)$">
    Header unset X-UA-Compatible
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

<IfModule mod_mime.c>

  # Audio
  AddType audio/mp4          m4a f4a f4b
  AddType audio/ogg          oga ogg opus

  # Data interchange
  AddType application/json    json map
  AddType application/ld+json jsonld

  # JavaScript
  # Normalize to standard type (it's sniffed in IE anyways):
  AddType application/javascript    js

  # Video
  AddType video/mp4          f4v f4p m4v mp4
  AddType video/ogg          ogv
  AddType video/webm         webm
  AddType video/x-flv         flv

  # Web fonts
  AddType application/font-woff    woff
  AddType application/vnd.ms-fontobject    eot

  # Browsers usually ignore the font MIME types and simply sniff the bytes to figure out

```

*the font type.*

*# Chrome however, shows a warning if any other MIME types are used for the following fonts.*

```
AddType application/x-font-ttf          ttc ttf
AddType font/opentype                   otf
```

*# Make SVGZ fonts work on iPad:*

```
AddType    image/svg+xml              svgz
AddEncoding gzip                       svgz
```

*# Other*

```
AddType application/octet-stream      safariextz
AddType application/x-chrome-extension  crx
AddType application/x-opera-extension   oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall         xpi
AddType application/xml                 atom rdf rss xml
AddType image/webp                      webp
AddType image/x-icon                    cur
AddType text/cache-manifest             appcache manifest
AddType text/vtt                        vtt
AddType text/x-component                htc
AddType text/x-vcard                    vcf
```

```
</IfModule>
```

```
# -----
```

*# UTF-8 encoding*

```
# -----
```

*# Use UTF-8 encoding for anything served text/plain or text/html*

```
AddDefaultCharset utf-8
```

*# Force UTF-8 for a number of file formats*

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
```

```
</IfModule>
```

```
# -----
```

*# Start rewrite engine*

```
# -----  
  
# Turn on the rewrite engine  
<IfModule mod_rewrite.c>  
    Options +FollowSymlinks  
    # Options +SymLinksIfOwnerMatch  
    RewriteEngine On  
    # RewriteBase /  
</IfModule>  
  
# rewrite www.domain.com to domain.com  
<IfModule mod_rewrite.c>  
    RewriteCond %{HTTPS} !=on  
    RewriteCond %{HTTP_HOST} ^www\.(.+) $ [NC]  
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]  
</IfModule>  
  
# -----  
# Redirects  
# -----  
  
# <IfModule mod_rewrite.c>  
# RewriteEngine On  
# RewriteCond %{HTTP_HOST} ^producteursdepoulet.armystage\.com [NC]  
# RewriteRule (.*) http://www.producteursdepoulet.armystage.com/$1 [L,R=301]  
# </IfModule>  
  
# Redirect 301 /courtyard http://ottawafringe.com/whats-on/fringe-courtyard  
  
# ErrorDocument 404 /404.html  
  
# -----  
# File access  
# -----  
  
# Block access to directories without a default document  
  
<IfModule mod_autoindex.c>  
    Options -Indexes  
</IfModule>
```

```
# -----

# Block access to hidden files and directories

<IfModule mod_rewrite.c>
  RewriteCond %{SCRIPT_FILENAME} -d [OR]
  RewriteCond %{SCRIPT_FILENAME} -f
  RewriteRule "(^/)\." - [F]
</IfModule>

# -----

# Block access to files that can expose sensitive information.

# By default, block access to backup and source files that may be left by some
# text editors and can pose a security risk when anyone has access to them.
# http://feross.org/cmsploit/

# IMPORTANT: Update the `<FilesMatch>` regular expression from below to include
# any files that might end up on your production server and can expose sensitive
# information about your website. These files may include: configuration files,
# files that contain metadata about the project (e.g.: project dependencies),
# build scripts, etc..

<FilesMatch "(^#.#|\.|(bak|config|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$" >

  # Apache < 2.3
  <IfModule !mod_authz_core.c>
    Order allow,deny
    Deny from all
    Satisfy All
  </IfModule>

</FilesMatch>

# #####
# # WEB PERFORMANCE
# #####

# -----

# Compression
```

```
# -----  
  
<IfModule mod_deflate.c>  
  
    # Force compression for mangled headers.  
    <IfModule mod_setenvif.c>  
        <IfModule mod_headers.c>  
            SetEnvIfNoCase ^(\Accept-EncodXng| X-cept-Encoding| X(15)| ^(15)| -(15))$  
            ^((gzip| deflate)\s*, ?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding  
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding  
        </IfModule>  
    </IfModule>  
  
    # Compress all output labeled with one of the following MIME-types  
    # (for Apache versions below 2.3.7, you don't need to enable 'mod_filter'  
    # and can remove the 'IfModule mod_filter.c' and '/IfModule' lines  
    # as 'AddOutputFilterByType' is still in the core directives).  
    # <IfModule mod_filter.c>  
    AddOutputFilterByType DEFLATE application/atom+xml \  
        application/javascript \  
        application/json \  
        application/rss+xml \  
        application/vnd.ms-fontobject \  
        application/x-font-ttf \  
        application/x-web-app-manifest+json \  
        application/xhtml+xml \  
        application/xml \  
        font/opentype \  
        image/svg+xml \  
        image/x-icon \  
        text/css \  
        text/html \  
        text/plain \  
        text/x-component \  
        text/xml  
  
    # </IfModule>  
  
</IfModule>  
  
# -----  
# ETag removal
```

```

# -----

# Since we're sending far-future expires headers (see below), ETags can be removed

<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

FileETag None

# -----

# Expires headers (for better cache control)
# -----

# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.

<IfModule mod_expires.c>

  ExpiresActive on
  ExpiresDefault "access plus 1 month"

  # CSS
  ExpiresByType text/css "access plus 1 year"

  # Data interchange
  ExpiresByType application/json "access plus 0 seconds"
  ExpiresByType application/xml "access plus 0 seconds"
  ExpiresByType text/xml "access plus 0 seconds"

  # Favicon (cannot be renamed!)
  ExpiresByType image/x-icon "access plus 1 week"

  # HTML components (HTCs)
  ExpiresByType text/x-component "access plus 1 month"

  # HTML
  ExpiresByType text/html "access plus 0 seconds"

  # JavaScript

```

```
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

```
</IfModule>
```