

DirectoryIndex index.php

```
<IfModule sapi_apache2.c>
    php_value register_globals      0
    php_value magic_quotes_gpc      0
    php_value magic_quotes_runtime  0
    php_value magic_quotes_sybase   0
    php_value arg_separator.output   "&"
    php_value default_charset        "utf-8"
    php_value session.name           "AK_SESSID"
</IfModule>

# On some servers this directive might be needed
# Options +FollowSymLinks

# Various rewrite rules
<IfModule mod_rewrite.c>
    RewriteEngine on

    RewriteRule ^(.*/)?\.(svn|git|hgl|bzt)/ - [F,L]
    ErrorDocument 403 "Access Forbidden"

# If your Akelos Framework application is accessed via an Alias directive,
# then you MUST also set the RewriteBase in this htaccess file.
#
# Example:
# Alias /myakelosapp /path/to/myakelosapp/public
# RewriteBase /

# If you don't want The Akelos Framework to look in certain directories,
# use the following rewrite rules so that Apache won't rewrite certain requests
#
# Example:
# RewriteCond %{REQUEST_URI} ^/notakelos.*
# RewriteRule .* - [L]

RewriteRule ^mod_rewrite_test$ mod_rewrite_test_file.txt [L]

# Rewrite URLs of the form 'index.php?ak=x':
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !favicon.ico$
RewriteRule ^(.*)$ index.php?ak=$1 [L,QSA]
```

```
</IfModule>
```

```
ErrorDocument 500 "<h2>Apache server error</h2>Akelos application failed to start properly"
```