

```
#####
#   type: CFG, HTTPD                               @ 2011-2015 Selivanovskikh M. G. #
# charset: UTF-8                                   #
# created: 2011. 01. 01                             #
#   path: .htaccess                                  #
#####
<Files ".*">
    Order Allow,Deny
    Deny from All
</Files>

###FileSystems
Options -Indexes
DirectoryIndex index.php
AddDefaultCharset Off
#ErrorDocument 400 "error400"

###Rewrite
RewriteEngine On
RewriteBase /

rewriteCond %{REQUEST_URI} !^/favicon.ico
rewriteCond %{REQUEST_URI} !^/trex/
rewriteCond %{REQUEST_URI} !^/dev/
rewriteCond %{REQUEST_URI} !^/core/theme/
rewriteCond %{REQUEST_URI} !^/modules/
rewriteCond %{REQUEST_URI} !^/phpPgAdmin/
rewriteCond %{REQUEST_URI} !^/index.php
rewriteCond %{REQUEST_URI} !^/cache/img
rewriteCond %{REQUEST_URI} !^/files
RewriteRule ^(.*)?(/*(.*))+ $ /index.php [L, QSA]

#Для получения POST raw data от multipart/form-data
<IfModule mod_setenvif>
    SetEnvIf Content-Type ^(multipart/form-data)(.*) MULTIPART_CTYPE=$1$2
    <IfModule mod_headers>
        RequestHeader set Content-Type application/x-httpd-php env=MULTIPART_CTYPE
        RequestHeader set X-Real-Content-Type %{MULTIPART_CTYPE}e env=MULTIPART_CTYPE
    </IfModule>
</IfModule>
```