

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
```

```
# Use options from the htaccess in the main directory of the frontend in order  
# to have versioned static files and TYPO3_CONTEXT working
```

```
RewriteOptions inherit
```

```
# Store the current location in an environment variable CWD to use  
# mod_rewrite in .htaccess files without knowing the RewriteBase
```

```
RewriteCond $0#%(REQUEST_URI) ([^#]*)#(.*)\1$
```

```
RewriteRule ^.*$ - [E=CWD:%2]
```

```
# Block non-existing .map files, which are requested by some browsers.  
# We need to do that this way here, because otherwise the rewrite logic  
# of the parent folder will redirect such a request to the typo3/index.php  
# causing the BE (login) to be returned.  
# This is due to the nature of 'RewriteOptions inherit', which copies the rules  
# virtually into this file (at the end) and then the defined rules, which include  
# 'typo3/' will not match in the context of this file.
```

```
RewriteRule \.map$ - [F]
```

```
# Redirect install tool files
```

```
RewriteRule ^install(\/?.*$) %(ENV:CWD)sysextd/install/Start/Install.php [R=307,L]
```

```
# Redirect old entry points
```

```
RewriteRule
```

```
^(ajax|alt_clickmenu|alt_db_navframe|alt_doc|alt_file_navframe|browser|db_new|dummy|init|log  
%(ENV:CWD)deprecated.php
```

```
</IfModule>
```