

## Options -Indexes

```
ErrorDocument 400 /error/view/400
ErrorDocument 401 /error/view/401
ErrorDocument 403 /error/view/403
ErrorDocument 404 /error/view/404
ErrorDocument 405 /error/view/405
ErrorDocument 408 /error/view/408
ErrorDocument 410 /error/view/410
ErrorDocument 411 /error/view/411
ErrorDocument 412 /error/view/412
ErrorDocument 413 /error/view/413
ErrorDocument 414 /error/view/414
ErrorDocument 415 /error/view/415
ErrorDocument 417 /error/view/417
ErrorDocument 500 /error/view/500
ErrorDocument 501 /error/view/501
ErrorDocument 502 /error/view/502
ErrorDocument 503 /error/view/503
```

```
# These headers are recommended for security reasons. If you set them in
# Apache, then you should set them to null in config/config.php. -- cwells
# Great resource: https://github.com/h5bp/server-configs-apache
#<IfModule mod_headers.c>
#   Header always set Strict-Transport-Security "max-age=16070400; includeSubDomains"
#   Header set X-Content-Type-Options "nosniff"

# These do not need to be set for all file types, so they are unset in those cases. --
cwells
#   Header set Content-Security-Policy "frame-ancestors 'none'"
#   Header set X-Frame-Options "DENY"
#   Header set X-XSS-Protection "1; mode=block"
#   <FilesMatch "\.
(appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpw]|flv|geojson|gif|htcl|icol|jpe?
|j|j|json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|webmanifest|woff2?|x|oc|x|xml|xpi)$">
#       Header unset Content-Security-Policy
#       Header unset X-Frame-Options
#       Header unset X-XSS-Protection
#       </FilesMatch>
```

```
# </FilesMatch>
#</IfModule>

DirectorySlash Off

RewriteEngine On
RewriteBase /

# Redirect www to non-www.
RewriteCond %{HTTP_HOST} ^www\.(.)*$ [NC]
RewriteRule ^(.)*$ https://%1/$1 [R=301,L]

# Redirect http to https.
RewriteCond %{HTTPS} !=on
RewriteRule ^ https://%(HTTP_HOST)%{REQUEST_URI} [R=301,L]

# Redirect root to the site index.
RewriteRule ^/?$ /site [R=302,QSA,L]

# If the URL ends with a trailing slash, remove it.
RewriteRule ^(.*)/$ $1 [R=302,QSA,L]

# Files inside the public directory and main.php are the only directly accessible files.
RewriteRule ^public/ - [L]
RewriteRule ^application/main\.php - [L]

# If the requested file path exists under the public directory, rewrite to the path inside
public.
RewriteCond %{DOCUMENT_ROOT}/public/%{REQUEST_URI} -f
RewriteRule ^(.+)$ public/$1 [QSA,L]

# All other URLs:
# If there is only one "directory" in the URL path, use it as the controller name and call
its default method.
RewriteRule ^([^\/]*)/?$ /application/main.php?controller=$1&method=index [QSA,L]
# Interpret more than one "directory" in the URL path as
/<controller>/<method>/<parameter>
RewriteRule ^([^\/]*)/([^\/]*)/(.*)?$ /application/main.php?
controller=$1&method=$2&parameter=$4 [QSA,L]
```