ErrorDocument 404 {{site.baseurl}}/404.html

turn on redirection Options +FollowSymLinks RewriteEngine on

```
# NOTE:
```

#	Some of the below redirects are 302s, and some are 301s. 302s are used
#	for redirects whose targets change sometimes. For example:
#	- /docs/ -> /docs/fr/, /docs/en/, etc.
#	- /docs/en/ -> /docs/en/dev/, /docs/en/latest/, etc.
#	– /docs/en/latest -> /docs/en/4,0,0/, /docs/en/5,0,0/, etc.
#	
#	301s are for PERMANENT redirects. These are used only for mapping old
#	pages to new pages.

```
# 302 (temp):
```

```
# docs -> docs/en/latest/
# docs/ -> docs/en/latest/
# docs/XX -> docs/XX/latest/
# docs/XX/ -> docs/XX/latest/
#
# HOTE:
# these can both apply, turning "/docs" into "/docs/en/latest/"
RewriteRule ^.*docs/$ ((site.baseurl))/docs/en/
```

RewriteRule ^.*docs/(\w\w)/\$ {{site.baseurl}}/docs/\$1/latest/ [R=302,L]

302 (temp): # docs/XX/latest -> docs/XX/latest/ RewriteRule ^.*docs/(\w\w)/latest\$ {(site.baseurl)}/docs/\$1/latest/ [R=302,L]

```
# 301 (perm);
# docs/XX/edge -> docs/xx/edge/
```

```
# _____docs/XX/edge/ -> docs/xx/dev/
```

```
RewriteRule ^.*docs/(\w\w)/edge$ {{site.baseurl}}/docs/$1/edge/
```

RewriteRule ^. *docs/(\w\w)/edge/(.*)\$ ({site.baseurl})/docs/\$1/dev/\$2 [R=301,L]

```
# зыі срегти:
        docs version renames
RewriteRule ^. *docs/(\w\w)/6.0.0/(.*)$ {{site.baseurl}}/docs/$1/6.x/$2 [R=301,L]
# 301 (perm):
       old docs pages -> new docs pages (global)
#
#
# NOTE:
        The first part of the path (i.e. the ".*") is thrown away and replaced
#
#
        by site baseurl. It is thrown away because there is no RewriteCond to
        control whether the rewrite happens to a URI or a local file path
#
        (when Apache is locating the local file to serve).
#
(% for redirect in site, data, redirects, docs-global %)RewriteRule
^. *docs/(\w\w)/([^/]+)/((redirect.old))$ ((site.baseurl))/docs/$1/$2/((redirect.new))
[NE, R=301, L]
{% endfor %}
```

```
# 301 (perm):
```

old docs pages -> new docs pages (version-specific)

(% for redirect in site data redirects docs %)RewriteRule ^. *docs/(\w\w)/{{redirect.old})\$
((site baseurl))/docs/\$1/{{redirect.new}} [NE, R=301, L]
(% endfor %)

```
# 301 (perm):
```

old pages -> new pages

```
(% for redirect in site data redirects general %)RewriteRule ^.*/((redirect.old))$
((site baseurl))/((redirect new)) [NE,R=301,L]
(% endfor %)
```

```
# rewrite onlu:
       /docs/XX/latest/* -> /docs/XX/Y, Y, Y/*
#
#
# NOTE:
        This does NOT return a redirect. It returns the resource *as if* the
#
        redirected URI was requested. That is, both URIs return the same
#
        resource, but the browser won't change the URI (no redirects followed).
#
# NOTE:
        This needs to be *after* the docs redirects because they might need the
#
        "/latest/" to be in the URI in order to activate. Placing this rule
#
        before them will rewrite "/latest/" to the latest version and redirects
#
        for "/latest/some/path.html" will never activate.
#
```

RewriteRule ".*docs/(\w\w)/latest/(.*)\$

{{site.baseurl}}/docs/\$1/{{site.latest_docs_version}}/\$2 [L]