

```
#-----  
# Who's Server root folder. File .htaccess  
# This file provides server security limiting access to the localhost only.  
# Comment next four lines to deactivate. (Allows external access)  
#-----  
  
Order Deny,Allow  
Deny from all  
Allow from 127.0.0.1  
Allow from ::1  
  
#-----  
# To allow execution of cgi scripts in this directory uncomment next two lines.  
#-----  
  
AddHandler cgi-script .pl .cgi  
Options +ExecCGI +FollowSymLinks  
  
#-----  
# Activate this section to use the Private Server Feature!  
# AuthName:      Replace with a suitable name appropriate to your site  
# AuthType:      Do not change  
# AuthUserFile:  .././.././htpasswd Corresponds to folder UniServer\htpasswd  
#                 In folder UniServer\htpasswd create a new folder e.g \host_1  
#                 In this new folder create a new file named .htpasswd  
#                 Edit this file and add a name and password for example  
#                 name123: password45  
#                 Path will look like this (replace xxx with your new folder):  
#                 .././.././htpasswd/\host_1/.htpasswd  
# Note: AuthUserFile - File path is relative to server root  
# To lock server, uncomment the next 4 lines. (A name and password is required)  
#-----  
  
#AuthName "Uniform Server - Server Access"  
#AuthType Basic  
#AuthUserFile .././.././htpasswd/xxx/.htpasswd  
#Require valid-user
```