

Don't show directory listings for URLs which map to a directory.

`Options -Indexes`

Make HTMLy handle any 404 errors.

`ErrorDocument 404 /index.php`

Set the default handler.

`DirectoryIndex index.php`

Requires mod_expires to be enabled.

`<IfModule mod_expires.c>`

to activate mode_expires

ExpiresActive on

ExpiresDefault

"access plus 1 month"

For CSS

ExpiresByType text/css

"access plus 1 month"

For Data interchange

ExpiresByType application/json

"access plus 0 seconds"

ExpiresByType application/xml

"access plus 0 seconds"

ExpiresByType text/xml

"access plus 0 seconds"

For Favicon

ExpiresByType image/x-icon

"access plus 1 year"

For HTML components (HTCs)

ExpiresByType text/x-component

"access plus 1 month"

For HTML

ExpiresByType text/html

"access plus 1 month"

For JavaScript

ExpiresByType text/js

"access plus 1 month"

ExpiresByType text/javascript

"access plus 1 month"

ExpiresByType application/javascript

"access plus 1 month"

ExpiresByType application/x-javascript

"access plus 1 month"

For Manifest files

```

# For manifest files
# ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
# ExpiresByType text/cache-manifest "access plus 0 seconds"

# For Media
# ExpiresByType audio/ogg "access plus 1 month"
# ExpiresByType image/gif "access plus 1 month"
# ExpiresByType image/jpeg "access plus 1 month"
# ExpiresByType image/png "access plus 1 month"
# ExpiresByType video/mp4 "access plus 1 month"
# ExpiresByType video/ogg "access plus 1 month"
# ExpiresByType video/webm "access plus 1 month"

# For Web feeds
# ExpiresByType application/atom+xml "access plus 1 day"
# ExpiresByType application/rss+xml "access plus 1 day"

# For Web fonts
# ExpiresByType application/font-woff "access plus 1 month"
# ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
# ExpiresByType application/x-font-ttf "access plus 1 month"
# ExpiresByType font/opentype "access plus 1 month"
# ExpiresByType image/svg+xml "access plus 1 month"

</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>

    RewriteEngine on

    # Uncomment the following to redirect all visitors to the https version
    # RewriteCond %{HTTPS} off
    # RewriteRule (.*) https://www.example.com/$1 [R=301,L]
    # RewriteCond %{HTTPS} on
    # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
    # RewriteRule (.*) https://www.example.com/$1 [R=301,L]

    # Uncomment the following to redirect all visitors to the www version
    # RewriteCond %{HTTP_HOST} !^www\. [NC]
    # RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

```

```

# Uncomment the following to redirect all visitors to non www version
# RewriteCond %{HTTP_HOST} ^www\. (.+)$ [NC]
# RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]

# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

# Pass all requests not referring directly to files in the filesystem to index.php.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^ index.php [L]

</IfModule>

# Enable Gzip compression.
<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
AddOutputFilterByType DEFLATE application/atom+xml \
    text/js \
    text/javascript \
    application/javascript \
    application/x-javascript \
    application/json \
    application/rss+xml \
    application/vnd.ms-fontobject \

```

```
application/x-font-ttf \  
application/x-web-app-manifest+json \  
application/xhtml+xml \  
application/xml \  
font/opentype \  
image/svg+xml \  
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml
```

</IfModule>