

```

# This file is part of FREE DEED POLL.org,
#
# Copyright © 2013 Deed Poll Office Ltd
#
# FREE DEED POLL.org is free software: you can redistribute it and/or modify
# it under the terms of the GNU Affero General Public License as
# published by the Free Software Foundation, either version 3 of the
# License, or (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU Affero General Public License for more details.
#
# You should have received a copy of the GNU Affero General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.

```

Options -MultiViews

```

<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge,chrome=IE6"
    # `mod_headers` can't match based on the content-type, however, we only
    # want to send this header for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|otf|pdf|png|safariextz|svgz?
|ttf|vcf|webapp|webm|webp|woff|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

<IfModule mod_mime.c>

# Audio
AddType audio/mp4          m4a f4a f4b
AddType audio/ogg          oga ogg

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript    js
AddType application/javascript    :----

```

```
AddType application/json json
```

Video

```
AddType video/mp4 mp4 m4v f4v f4p
```

```
AddType video/ogg ogv
```

```
AddType video/webm webm
```

```
AddType video/x-flv flv
```

Web fonts

```
AddType application/font-woff woff
```

```
AddType application/vnd.ms-fontobject eot
```

*# Browsers usually ignore the font MIME types and sniff the content,
however, Chrome shows a warning if other MIME types are used for the
following fonts.*

```
AddType application/x-font-ttf ttc ttf
```

```
AddType font/opentype otf
```

Make SVGZ fonts work on iPad:

<https://twitter.com/FontSquirrel/status/14855840545>

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

Other

```
AddType application/octet-stream safariextz
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-shockwave-flash swf
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/xml atom rdf rss xml
```

```
AddType image/webp webp
```

```
AddType image/x-icon ico
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/vtt vtt
```

```
AddType text/x-component htc
```

```
AddType text/x-vcard vcf
```

```
</IfModule>
```

```
AddDefaultCharset utf-8
```

```
# Force UTF-8 for certain file formats.
<IfModule mod_mime.c>
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

Redirect 404 /LICENSE
Redirect 404 /README.md
Redirect 404 /robots.txt.php

<IfModule mod_rewrite.c>
    Options +FollowSymlinks
    # Options +SymLinksIfOwnerMatch
    RewriteEngine On
    # RewriteBase /

    # Redirect www to naked domain
    RewriteCond %{HTTP_HOST} ^www\.(.+) [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]

    # Redirect http to https
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} !^dev\..
    RewriteRule ^(.*) https://%(SERVER_NAME)/$1 [NE,R=301,L]

    # Strip trailing slashes
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(.+)/+$ http://%(HTTP_HOST)/$1 [R=301,L]

    RewriteCond %{REQUEST_URI}::$1 ^(/.+)/(.*)::\2$
    RewriteRule ^(.*) - [E=BASE:%1]

    RewriteCond %{ENV:REDIRECT_STATUS} ^$
    RewriteRule ^app\.php(/(.*)|)$ %(ENV:BASE)/$2 [R=301,L]

    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [L,R=404]

    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
```

```

RewriteRule "(^|/)\." - [L,R=404]

RewriteCond %{SCRIPT_FILENAME} -d [OR]
RewriteCond %{SCRIPT_FILENAME} -f
RewriteRule "(^|/)\." - [L,R=404]

# If requested filename exists, serve it
RewriteCond %{REQUEST_FILENAME} -f
RewriteRule .? - [L]

# Rewrite all other queries to the front controller
RewriteRule .? %{ENV:BASE}/index.php [L]

# Versioning on static resources
RewriteRule ^(.(+)\.v[0-9.]+\.(js|css|png|jpg|gif|ico))$ $1.$2 [L]
</IfModule>

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

<FilesMatch "(^#.#\.(bak|config|dist|fla|inc|ini|log|psd|sh|sql|sw[op])|\.")$" >
    Require all denied
</FilesMatch>

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives).

```

```
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# Prevent some of the mobile network providers from modifying the content of  
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html #sec14.9.5.
```

```
# <IfModule mod_headers.c>  
#   Header set Cache-Control "no-transform"  
# </IfModule>
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

```
FileETag None
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```

ExpiresByType text/css "access plus 1 year"

# Data interchange
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"

# Favicon (cannot be renamed!)
ExpiresByType image/x-icon "access plus 1 week"

# HTML components (HTCs)
ExpiresByType text/x-component "access plus 1 month"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"

```

ExpiresByType image/svg+xml

"access plus 1 month"

</IfModule>