

```

<IfModule mod_rewrite.c>
  <IfModule mod_negotiation.c>
    Options -MultiViews
  </IfModule>

  RewriteEngine On

  RewriteRule ^(.*)/$ /$1 [L,R=301]

  # -----
  # www redirect
  # -----
  # RewriteCond %{HTTPS} !=on
  # RewriteCond %{HTTP_HOST} !^www\. .+$ [NC]
  # RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]

  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteRule ^ index.php [QSA,L]
</IfModule>

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml .txt

# -----
# Defining new MIME types
# -----
<IfModule mod_mime.c>
  AddType application/vnd.ms-fontobject eot
  AddType application/x-font-ttf ttf ttc
  AddType font/opentype otf
  AddType application/x-font-woff woff
</IfModule>

#

```

```

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

    # Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-
    beyond-gzipping/
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$
            ^((gzip|deflate)\s*,?\s*)+ [X"]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
    # `AddOutputFilterByType` is still in the core directives)
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \
            application/rss+xml \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            application/xhtml+xml \
            application/xml \
            font/opentype \
            image/svg+xml \
            image/x-icon \
            text/css \
            text/html \
            text/plain \
            text/x-component \
            text/xml \
            text/javascript \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            font/opentype \
            text/css \
            text/html \
            text/javascript \
            text/plain \
            text/xml \
            text/xml-external-parsed-entity \
            text/xml-script \
            text/xml-script-set \
            text/xml-stylesheet \
            text/xml-xsl \
            text/xml-xslt
    </IfModule>

```

```
application/x-font-woff
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
<FilesMatch "\.
```

```
(ico|pdf|flv|jpg|jpeg|svg|png|gif|swf|js|xml|txt|css|woff|ttf|ttd|eot|otf)$">
```

```
Header set Cache-Control "max-age=604800, public"
```

```
</FilesMatch>
```

```
</IfModule>
```