

```
#####
## Simple rewrite URL's
#####

RewriteRule ^products(/)?$ products.html [L]
RewriteRule ^product/detail(/)?$ products-detail.html [L]
RewriteRule ^about(/)?$ about.html [L]

#####
## HTML5 proper mime-type for manifest files
#####

<IfModule mime_module>
  AddType text/cache-manifest .appcache .manifest
</ifModule>

#####
## Cache settings for the manifest file
#####

<IfModule mod_expires.c>
  Header set cache-control: public
  ExpiresActive on

  #####
  ## Prevent receiving a cached manifest
  #####

  ExpiresByType text/cache-manifest "access plus 0 seconds"
</IfModule>

#####
## Check for mod_rewrite module
#####

<IfModule mod_rewrite.c>

  #####
  ## Turn mod_rewrite on
  #####
```

RewriteEngine On

```
#####  
## Strip out the version number off the request URL  
## Incoming: header, v2, gif  
## Outgoing: header, gif  
#####
```

RewriteRule ^(\. *\.)v[0-9]+\.(css|js|gif|jpe?g|png|ico|pdf|swf|flv|mov|mpe?g|avi)\$ \$1\$2

```
#####  
## Check the original URL request and if a version number  
## is present; if so, add the environmental variable  
#####
```

```
RewriteCond %{THE_REQUEST} ^(\GET|HEAD)\ (\. *\. )v[0-9]+\.(css|js|gif|jpe?  
g|png|ico|pdf|swf|flv|mov|mpe?g|avi)\ HTTP/1.(0|1)  
RewriteRule ^.*$ - [NC,L,E=request_url_versioned:yes]  
</IfModule>
```

```
#####  
## Check for mod_headers module  
#####
```

<IfModule mod_headers.c>

```
#####  
## Filter incoming requests of these file types and only add the  
## expire-header if the environmental variable is true/yes  
#####
```

```
<FilesMatch "\.(css|js|gif|jpe?g|png|ico|pdf|swf|flv|mov|mpe?g|avi)$">  
  Header set Expires "Thu, 31 Dec 2013 20:00:00 GMT" env=request_url_versioned  
  Header unset ETag env=request_url_versioned  
</FilesMatch>  
</IfModule>
```

```
#####  
## Remove the eTag from the header  
#####
```

```
<ifModule mod_headers.c>
  Header unset ETag
</ifModule>
```

FileETag None

```
#####
## Check for mod_mime module
#####
```

```
<IfModule mod_mime.c>
```

```
#####
## Set default UTF-8 encoding
#####
```

```
AddDefaultCharset utf-8
```

```
#####
## Force utf-8 for a number of file formats
#####
```

```
AddCharset utf-8 .html? .css .js .xml .json .rss
```

```
</IfModule>
```