```
# In case you want to add a .htpasswd authentification
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentification
# Example:
# Order Deny,Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any

<IfModule mod_rewrite.c>
Options +FollowSymLinks
RewriteEngine On
RewriteBase /oxidShopdev

RewriteCond %{REQUEST_URI}      config\.inc\.php [NC]
RewriteRule ^config\.inc\.php   index\.php          [R=301,L]

RewriteCond %{QUERY_STRING}      fnc=(getShopVersion|getShopEdition|getRevision) [NC]
RewriteRule ^(.*)$               $1?                                              [R=301,L]

RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]

RewriteCond %{REQUEST_URI} oxseo\.php$
RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
RewriteRule oxseo\.php$ oxseo.php?mod_rewrite_module_is=on [L]

RewriteCond %{REQUEST_URI} !
(\/admin\/|\/core\/|\/application\/|\/export\/|\/modules\/|\/out\/|\/setup\/|\/tmp\/|\/views
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule !(\.html|\/|\.jpg|\.css|\.pdf|\.doc|\.gif|\.png|\.js|\.htc|\.svg)$ %{REQUEST_URI
[R=301,L]

RewriteCond %{REQUEST_URI} !
(\/admin\/|\/core\/|\/application\/|\/export\/|\/modules\/|\/out\/|\/setup\/|\/tmp\/|\/views
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.html|\/)$ oxseo.php


RewriteCond %{REQUEST_URI} (\/out\/pictures\/)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.jpe?g|\.gif|\.png|\.svg)$ getimg.php


</IfModule>


# disabling log file access from outside
<FilesMatch "(EXCEPTION_LOG\.txt|\.log$|\.tpl$|pkg\.rev|\.ini|pkg\.info|\.pem$)">
order allow,deny
deny from all
</FilesMatch>


Options -Indexes
DirectoryIndex index.php index.html
```