

```

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xhtml|svn-
base)$|^(\code-style|\.p1|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
    php_value mbstring.http_input        pass
    php_value mbstring.http_output       pass
    php_value mbstring.encoding_translation 0

```

```
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 4, Apache 2.*

```
<IfModule sapi_apache2.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 5, Apache 1 and 2.*

```
<IfModule mod_php5.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# Requires mod\_expires to be enabled.*

```
<IfModule mod_expires.c>
```

*# Enable expirations.*

```
ExpiresActive On
```

*# Cache all files for 2 weeks after access (A).*

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

*# Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod\_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.*

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

... ..

```

# Various rewrite rules.
<IfModule mod_rewrite.c>
  RewriteEngine on

  # If your site can be accessed both with and without the 'www.' prefix, you
  # can use one of the following settings to redirect users to your preferred
  # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
  #
  # To redirect all users to access the site WITH the 'www.' prefix,
  # (http://example.com/... will be redirected to http://www.example.com/...)
  # adapt and uncomment the following:
  # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
  # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
  #
  # To redirect all users to access the site WITHOUT the 'www.' prefix,
  # (http://www.example.com/... will be redirected to http://example.com/...)
  # uncomment and adapt the following:
  # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
  # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

  # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
  # VirtualDocumentRoot and the rewrite rules are not working properly.
  # For example if your site is at http://example.com/drupal uncomment and
  # modify the following line:
  # RewriteBase /drupal
  #
  # If your site is running in a VirtualDocumentRoot at http://example.com/,
  # uncomment the following line:
  # RewriteBase /

  ### BOOST START ###

  # NORMAL - Cached css & js files
  RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css -s
  RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.css [L,QSA,T=text/css]
  RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js -s
  RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\.js [L,QSA,T=text/javascript]

  # Caching for anonymous users
  # Skip boost IF not get request OR uri has wrong dir OR cookie is set OR request came
  # from this server OR https request
  RewriteCond %{REQUEST_METHOD} !^(GET|HEAD)$ [OR]

```

```
RewriteCond %{REQUEST_URI}
(<^(/admin/|cache/|misc/|modules/|sites/|system/|openid/|themes/|node/add/|comment/reply/)|
</edit/|user/|user/<(login/|password/|register)/>)$) [OR]
RewriteCond %{HTTP: Pragma} no-cache [OR]
RewriteCond %{HTTP: Cache-Control} no-cache [OR]
RewriteCond %{HTTPS} on [OR]
RewriteCond %{HTTP_COOKIE} DRUPAL_UID
RewriteRule .* - [S=1]

# NORMAL
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%
{QUERY_STRING}\.html -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html
[L, T=text/html]

### BOOST END ###

# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id$
```