

```

# Restricted access to files
<FilesMatch "(\\.
(lock|cachel db)|installed. json| composer. json| package. json| bower. json| CHANGELOG. md| README. m
# Apache < 2.3
<IfModule !mod_authz_core.c>
    Order allow,deny
    Deny from all
    Satisfy All
</IfModule>

# Apache ≥ 2.3
<IfModule mod_authz_core.c>
    Require all denied
</IfModule>
</FilesMatch>

# Don't show directory listings
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# URL rewrites
<IfModule mod_rewrite.c>
    RewriteEngine On

# Set base if your site is running in a VirtualDocumentRoot
# RewriteBase /

# Redirect requests to access the site with the 'www.' prefix
# RewriteCond %{HTTP_HOST} .
# RewriteCond %{HTTP_HOST} !^www\\. [NC]
# RewriteRule ^ https://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

# Redirect requests to access the site without the 'www.' prefix
# RewriteCond %{HTTP_HOST} ^www\\. (.+)$ [NC]
# RewriteRule ^ https://%1%{REQUEST_URI} [L,R=301]

# Redirect requests to access the site with HTTPS
# RewriteCond %{HTTPS} off
# RewriteRule ^ https://%{HTTP_HOST}%{REQUEST_URI} [L,R]

```

```
# Rewrite request to use the index.php
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^ index.php [L]

<IfModule mod_env.c>
    SetEnv HTTP_MOD_REWRITE On
</IfModule>

<IfModule !mod_env.c>
    <IfModule mod_headers.c>
        RequestHeader set MOD_REWRITE "On"
    </IfModule>
</IfModule>
</IfModule>

# Redirect admin URL, if rewrite is not enabled
<IfModule !mod_rewrite.c>
    <IfModule mod_alias.c>

        RedirectMatch (.*)?(?!index.php)\/admin$ $1/index.php/admin

    </IfModule>
</IfModule>

# Media types
<IfModule mod_mime.c>
    AddType image/svg+xml svg svgz

    <IfModule mod_deflate.c>
        AddEncoding gzip svgz
    </IfModule>
</IfModule>

# Normalize javascript mime type
<IfModule mod_mime.c>
    AddType application/javascript js
</IfModule>

# Compression
```

```

<IfModule mod_deflate.c>
    # Force compression for mangled `Accept-Encoding` request headers
    # https://developer.yahoo.com/blogs/ydn/pushing-beyond-gzipping-25601.html
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|def
Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE "application/javascript" \
            "application/json" \
            "application/rss+xml" \
            "image/bmp" \
            "image/svg+xml" \
            "image/x-icon" \
            "text/css" \
            "text/html" \
            "text/plain"

    </IfModule>
</IfModule>

# Expire headers
<IfModule mod_expires.c>
    ExpiresActive on
    ExpiresDefault          "access plus 1 week"

    ExpiresByType application/json          "access plus 0 seconds"
    ExpiresByType application/rss+xml      "access plus 0 seconds"
    ExpiresByType text/html                "access plus 0 seconds"
    ExpiresByType text/plain               "access plus 0 seconds"

    # Use expires far in the future for css and javascript because Pagekit uses filenames to
    ExpiresByType text/css                  "access plus 1 year"
    ExpiresByType application/javascript    "access plus 1 year"
</IfModule>

# Avoid PHP 5.6 deprecated $HTTP_RAW_POST_DATA warnings
<IfModule mod_php5.c>

```

```
php_value always_populate_raw_post_data -1
</IfModule>
```