

AddDefaultCharset UTF-8

php_value date.timezone "Europe/Berlin"

<IfModule mod_deflate.c>

Header add X-Enabled mod_deflate

</IfModule>

<IfModule mod_gzip.c>

Header add X-Enabled mod_gzip

</ifModule>

<IfModule mod_rewrite.c>

RewriteEngine on

RewriteBase /

RewriteRule ^res/. *\$ - [L]

RewriteRule ^lib/(.*)\$ index.php?class=\$1 [QSA,L]

RewriteRule ^id/(.*)\$ index.php?id=\$1 [QSA,L]

RewriteRule ^adm/id/(\d*). *\$ index.php?id=\$1 [QSA,L]

RewriteRule ^adm/. *\.(jpg|jpeg|gif|css|swf|png|js|xml|pdf|ico|html|eot|svg|ttf|woff). *\$ -
[NC,L]

RewriteRule ^adm/edit/(.*)\$ index.php?edit=1&id=\$1 [QSA,L]

RewriteRule ^adm/preview/(.*)\$ index.php?preview=1&id=\$1 [QSA,L]

RewriteRule ^adm/(.*)\$ adm/index.php?\$1 [QSA,L]

RewriteCond %{DOCUMENT_ROOT}/application/data/cachetransparent/data%(REQUEST_URI) -f

RewriteRule ^(.*)\$ application/data/cachetransparent/data%(REQUEST_URI) [L]

RewriteRule ^skins/(.*)\$ application/skins/\$1 [L]

RewriteRule ^image/(.*)\$ index.php?imageurl=\$1 [QSA,L]

RewriteRule ^file/download/(.*)\$ index.php?fileurl=\$1 [QSA,L]

RewriteRule ^file/(.*)\$ index.php?&fileurl=\$1&inline=1 [QSA,L]

RewriteRule ^.(.*)\.(.*)\.minime.(.*)\$ index.php?minify=\$1&type=\$2 [QSA,L]

RewriteRule ^skin/(.*)\$ index.php?skinsource=\$1 [QSA,L]

RewriteRule ^font/(.*)\$ index.php?fonturl=\$1 [QSA,L]

```
RewriteRule sitemap.xml index.php?create=sitemap&format=xml [QSH,L]
```

```
RewriteRule ^.*\.
```

```
(php|jpg|jpeg|gif|css|swf|doc|txt|xls|png|js|xml|pdf|ico|htc|eot|svg|ttf|woff).*$ - [NC,L]
```

```
RewriteRule ^([\^()]*\([\^()]*\))$ index.php?url=$1&renderOnly=$2 [QSA,L]
```

```
RewriteRule ^(.*)$ index.php?url=$1 [QSA,L]
```

```
</IfModule>
```

```
<Files .htaccess>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
<Files config.json>
```

```
order allow,deny
```

```
deny from all
```

```
</Files>
```

```
# if problems occur - i.e. with file uploads - uncomment the next line
```

```
#php_value suhosin.session.cryptua 0
```