

```
<IfModule mod_rewrite.c>
  RewriteEngine On

  #####
  # ROUTER      #
  #####
  # get router by router_id (api/rest/router/router_id)
  RewriteRule ^router/([0-9]+)/?$ api.php?request=router&router_id=$1 [QSA,L]
  # get router by hostname (api/rest/router/hostname)
  RewriteRule ^router/([a-zA-Z0-9.-]+)/?$ api.php?request=router&hostname=$1 [QSA,L]

  #####
  # ROUTERLIST  #
  #####
  # routerlist containig all routers (api/rest/routerlist)
  RewriteRule ^routerlist/?$ api.php?request=routerlist [QSA,L]
  #routerlist containing all routers of a special user (api/rest/user/user_id/routerlist)
  RewriteRule ^user/([0-9]+)/routerlist/?$ api.php?request=routerlist&user_id=$1 [QSA,L]

  #####
  # NETWORKINTERFACE #
  #####
  # api/rest/networkinterfacelist/networkinterface_id
  RewriteRule ^networkinterface/([0-9]+)/?$ api.php?request=networkinterface&id=$1 [QSA,L]

  #####
  # NETWORKINTERFACELIST #
  #####
  # networkinterfacelist containig all networkinterfaces (api/rest/networkinterfacelist)
  RewriteRule ^networkinterfacelist/?$ api.php?request=networkinterfacelist [QSA,L]
  # networkinterfacelist containig all networkinterfaces of a special router
  (api/rest/router_id/networkinterfacelist)
  RewriteRule ^router/([0-9]+)/networkinterfacelist/?$ api.php?
request=networkinterfacelist&router_id=$1 [QSA,L]

  #####
  # IP          #
  #####
  # api/rest/ip/ip_id
  RewriteRule ^ip/([0-9]+)/?$ api.php?request=ip&id=$1 [QSA,L]
```

```
#####
# IPLIST #
#####
# iplist containing all ip addresses (api/rest/iplist)
RewriteRule ^iplist/?$ api.php?request=iplist [QSA,L]
# iplist containing all ip addresses of a special networkinterface
(api/rest/networkinterface/networkinterface_id/iplist)
RewriteRule ^networkinterface/([0-9]+)/iplist/?$ api.php?request=iplist&interface_id=$1
[QSA,L]
# iplist containing all ip addresses of a special network
(api/rest/network/network_id/iplist)
RewriteRule ^network/([0-9]+)/iplist/?$ api.php?request=iplist&network_id=$1 [QSA,L]

#####
# NETWORK #
#####
# api/rest/network/network_id
RewriteRule ^network/([0-9]+)/?$ api.php?request=network&network_id=$1 [QSA,L]

#####
# NETWORKLIST #
#####
# networklist containing all networks (api/rest/networklist)
RewriteRule ^networklist/?$ api.php?request=networklist [QSA,L]

#####
# DNS-ZONE #
#####
# api/rest/dns_zone/dns_zone_id
RewriteRule ^dns_zone/([0-9]+)/?$ api.php?request=dns_zone&id=$1 [QSA,L]

#####
# DNS-ZONE-LIST #
#####
# dns zone list containing all dns-zones (api/rest/dns_zone_list)
RewriteRule ^dns_zone_list/?$ api.php?request=dns_zone_list [QSA,L]
# dns zone list containing all dns-zones of a special user
(api/rest/user/user_id/dns_zone_list)
RewriteRule ^user/([0-9]+)/dns_zone_list/?$ api.php?request=dns_zone_list&user_id=$1
[QSA,L]
```

```

#####
# DNS-RESSOURCE-RECORD #
#####
# api/rest/dns_ressource_record/dns_ressource_record_id
RewriteRule ^dns_ressource_record/([0-9]+)/?$ api.php?request=dns_ressource_record&id=$1
[QSA, L]

#####
# DNS-RESSOURCE-RECORD-LIST #
#####
# dns ressource record list containing all ressource record
(api/rest/dns_ressource_record_list/)
RewriteRule ^dns_ressource_record_list/?$ api.php?request=dns_ressource_record_list
[QSA, L]
# dns ressource record list containing all ressource records of a special dns_zone
(api/rest/dns_zone/dns_zone_id/dns_ressource_record_list/)
RewriteRule ^dns_zone/([0-9]+)/dns_ressource_record_list/?$ api.php?
request=dns_ressource_record_list&dns_zone_id=$1 [QSA, L]
# dns ressource record list containing all ressource records of a special user
(api/rest/user/user_id/dns_ressource_record_list/)
RewriteRule ^user/([0-9]+)/dns_ressource_record_list/?$ api.php?
request=dns_ressource_record_list&user_id=$1 [QSA, L]

#####
# ORIGINATOR-STATUS-LIST #
#####
# originator status list containing all batman advanced originators
(api/rest/originator_status_list/)
RewriteRule ^originator_status_list/?$ api.php?request=originator_status_list [QSA, L]
# originator status list containing all batman advanced originators of a special router
(api/rest/router/router_id/originator_status_list/)
RewriteRule ^router/([0-9]+)/originator_status_list/?$ api.php?
request=originator_status_list&router_id=$1 [QSA, L]

#####
# EVENT #
#####
# api/rest/event/event_id
RewriteRule ^event/([0-9]+)/?$ api.php?request=event&id=$1 [QSA, L]
RewriteRule ^event/?$ api.php?request=event [QSA, L]

```

```
#####
# EVENTLIST #
#####
# eventlist containing all events known to netmon (api/rest/eventlist)
RewriteRule ^eventlist/?$ api.php?request=eventlist [QSA,L]
# eventlist containing all events of a special router
(api/rest/router/router_id/eventlist)
RewriteRule ^router/([0-9]+)/eventlist/?$ api.php?request=eventlist&router_id=$1 [QSA,L]

#####
# CONFIG #
#####
# config by id (api/rest/config/config_id)
RewriteRule ^config/([0-9]+)/?$ api.php?request=config&id=$1 [QSA,L]
# config by name (api/rest/config/name)
RewriteRule ^config/([0-9A-Za-z_-]+)/?$ api.php?request=config&name=$1 [QSA,L]

#####
# CONFIGLIST #
#####
# configlist containing all configs known to netmon (api/rest/configlist/)
RewriteRule ^configlist/?$ api.php?request=configlist [QSA,L]

#####
# CRAWL-CYCLE #
#####
# crawl_cycle by id (api/rest/config/crawl_cycle)
#RewriteRule ^crawl_cycle/([0-9]+)/?$ api.php?request=crawl_cycle&id=$1 [QSA,L]

#####
# CRAWL-CYCLE-LIST #
#####
# crawl_cycle_list containing all crawl_cycles known to netmon
(api/rest/crawl_cycle_list/)
RewriteRule ^crawl_cycle_list/?$ api.php?request=crawl_cycle_list [QSA,L]
</IfModule>
```