

```

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engineincl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\. php)?
|xml|)$|^(\. .*|Entries.*|Repository|Root|Tag|Template)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Multiviews creates problems with aliased URLs and is not needed for Drupal.
Options -Multiviews

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Override PHP settings that cannot be changed at runtime. See
# sites/default/default.settings.php and drupal_initialize_variables() in
# includes/bootstrap.inc for settings that can be changed at runtime.

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc                off
    php_flag magic_quotes_sybase             off
    php_flag register_globals                 off
    php_flag session.auto_start              off
    php_value mbstring.http_input             pass
    php_value mbstring.http_output           pass
    php_flag short_open_tag                   off

```

```

php_flag modstring.encoding_translation    Off
</IfModule>

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

<FilesMatch \.php$>
    # Do not allow PHP scripts to be cached unless they explicitly send cache
    # headers themselves. Otherwise all scripts would have to overwrite the
    # headers set by mod_expires if they want another caching behavior. This may
    # fail if an error occurs early in the bootstrap process, and it may cause
    # problems if a non-Drupal PHP file is installed in a subdirectory.
    ExpiresActive Off
</FilesMatch>
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteBase /

    #Removes access to the system folder by users.
    #Additionally this will allow you to create a System.php controller,
    #previously this would not have been possible.
    #'system' can be replaced if you have renamed your system folder.
    RewriteCond %{REQUEST_URI} ^system.*
    RewriteRule ^(.*)$ /index.php?/$1 [L]

    #When your application folder isn't in the system folder
    #This snippet prevents user access to the application folder
    #Submitted by: Fabdro1
    #Rename 'application' to your applications folder name.
    RewriteCond %{REQUEST_URI} ^application.*
    RewriteRule ^(.*)$ /index.php?/$1 [L]

    #Checks to see if the user is attempting to access a valid file,
    #and if not, redirect to the front page.

```

```
#such as an image or css document, if this isn't true it sends the  
#request to index.php  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteRule ^(.*)$ index.php?/$1 [L]  
</IfModule>  
  
<IfModule !mod_rewrite.c>  
# If we don't have mod_rewrite installed, all 404's  
# can be sent to index.php, and everything works as normal.  
# Submitted by: ElliotHaughin  
  
ErrorDocument 404 /index.php  
</IfModule>
```