```apache
RewriteEngine On
RewriteBase /

# Requests to the root
RewriteRule ^$ http://p3.fusepool.eu [R=301,L]

AddDefaultCharset utf-8
AddType text/turtle .ttl

# Rules based on http://www.wikier.org/blog/easily-document-your-vocabularies-ontologies-wi

# Rewrite rule to serve HTML content from the vocabulary URI if requested
RewriteCond %{HTTP_ACCEPT} !text/turtle.*(text/html|application/xhtml\+xml)
RewriteCond %{HTTP_ACCEPT} text/html [OR]
RewriteCond %{HTTP_ACCEPT} application/xhtml\+xml [OR]
RewriteCond %{HTTP_USER_AGENT} ^Mozilla/.*
RewriteCond %{REQUEST_FILENAME}.ttl -f
RewriteRule ^([a-z0-9]+)$ http://idi.fundacionctic.org/parrot/parrot?
documentUri=http://vocab.fusepool.info/$1.ttl&&customizeCssUrl=http://vocab.fusepool.info/st

# Rewrite rule to serve RDF content from the vocabulary URI if requested
RewriteCond %{HTTP_ACCEPT} text/turtle
RewriteCond %{REQUEST_FILENAME}.ttl -f
RewriteRule ^([a-z0-9]+)$ $1.ttl [R=303,L]

# Rewrite rule to serve the RDF content from the vocabulary URI by default
RewriteCond %{REQUEST_FILENAME}.ttl -f
RewriteRule ^([a-z0-9]+)$ $1.ttl [R=303]

# Deprecated namespaces
RewriteRule ^ldp$ elpd [R=301,L]
```